

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 160AMP 690V AM SIZE 2 DUAL IND - Fuse-link, low voltage, 160 A, AC 690 V, 120 kA, NH2, aM, IEC, dual indicator, live gripping lugs



160NHM2B-690 NH FUSE 160AMP 690V AM SIZE 2 DUAL IND

[Overview](#) [Specifications](#) [Resources](#)



160NHM2B-690 NH FUSE 160AMP 690V AM SIZE 2 DUAL IND

Fuse-link, low voltage, 160 A, AC 690 V, 120 kA, NH2, aM, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664153

Fuse, fuse-link, low voltage, 160 A, AC 690 V, NH2, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
160 A
Rated voltage
AC 690 V
Construction size
NH2
Utilization category
aM

Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
NH2
Rated current
160 A
Rated voltage
690 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
aM (switchgear protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo



Declaration of Conformity

EU

- 690V fuse-links with blade contacts (NH fuse system). Motor rated (DA-DC-00003508)

Asset
(PDF)

UK

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00004040\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)
[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH