

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 100AMP 690V aM SIZE 1 DUAL IND - Fuse-link, low voltage, 100 A, AC 690 V, 120 kA, NH1, aM, IEC, dual indicator, live gripping lugs



100NHM1B-690 NH FUSE 100AMP 690V aM SIZE 1 DUAL IND

[Overview](#) [Specifications](#) [Resources](#)



100NHM1B-690 NH FUSE 100AMP 690V aM SIZE 1 DUAL IND

Fuse-link, low voltage, 100 A, AC 690 V, 120 kA, NH1, aM, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664149

Fuse, Fuse-link, low voltage, 100 A, AC 690 V, NH1, aM, IEC, dual indicator, square body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA, Optional accessories fuse-holder SD1-D



•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
100 A
Rated voltage
AC 690 V
Construction size
NH1
Utilization category
aM

Status indicator
 dual indicator
 Description
 live gripping lugs
 Breaking Capacity
 120 kA
 usable for size/applications
 industrial
 Standard/Approval
 IEC
 Shape
 square body with knife blade contacts
 Standards/Regulations
 IEC 60269-2 fuse system A
 DIN 43620
 VDE 0636-2
 Optional accessories
 fuse-holder SD1-D

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
 Low-Voltage HRC fuse (ec@ss10.0.1-27-14-20-05 [AFZ800015])
 Construction size
 NH1
 Rated current
 100 A
 Rated voltage
 690 V
 Voltage type
 AC
 Rated switching capacity
 120 kA
 Utilization category
 aM (switchgear protection)
 Type of fuse status indicator
 Combination fuse status indicator
 Insulated metal gripping lugs (IMGL)
 No

Product photo



[160nhm1b-690_c](#)

Photo

•



[160NHM1B-690_l](#)

Photo

• □

[160NHM1B-690_r](#)

Photo

Declaration of Conformity

EU

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00003508\)](#)

Asset

(PDF)

UK

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00004040\)](#)

Asset

(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

