

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 200AMP 690V gG SIZE 2 DUAL IND - Fuse-link, low voltage, 200 A, AC 690 V, 120 kA, NH2, gL/gG, IEC, dual indicator, live gripping lugs



200NHG2B-690 NH FUSE 200AMP 690V gG SIZE 2 DUAL IND

[Overview](#) [Specifications](#) [Resources](#)



200NHG2B-690 NH FUSE 200AMP 690V gG SIZE 2 DUAL IND

Fuse-link, low voltage, 200 A, AC 690 V, 120 kA, NH2, gL/gG, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664122

Fuse, fuse-link, low voltage, 200 A, AC 690 V, NH2, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
200 A
Rated voltage
AC 690 V
Construction size
NH2
Utilization category
gL/gG

Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
NH2
Rated current
200 A
Rated voltage
690 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
gL/gG (cable protection/equipment protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo



Declaration of Conformity

EU

- Size 2, 690V fuse-links with blade contacts (NH fuse system) (DA-DC-00003480)

Asset
(PDF)

UK

- [Size 2, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004050\)](#)

Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

