

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 10AMP 690V SIZE 000 GG MGL - Fuse-link, low voltage, 10 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs



10NHG000B-690 NH FUSE 10AMP 690V SIZE 000 GG MGL

[Overview](#) [Specifications](#) [Resources](#)



## 10NHG000B-690 NH FUSE 10AMP 690V SIZE 000 GG MGL

Fuse-link, low voltage, 10 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs  
EL-Nummer (Norway) 1664098

Fuse, fuse-link, low voltage, 10 A, AC 690 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



•



•



•



•



•

Delivery program

•

Technical data ETIM 7.0

### Delivery program

Product range

Fuse  
 Basic function  
 Fuse-link  
 Field of application  
 low voltage  
 Rated current [I]  
 10 A  
 Rated voltage  
 AC 690 V  
 Construction size  
 NH000  
 Utilization category  
 gL/gG  
 Status indicator  
 dual indicator  
 Description  
 live gripping lugs  
 Breaking Capacity  
 120 kA  
 usable for size/applications  
 industrial  
 Standard/Approval  
 IEC  
 Shape  
 square body with knife blade contacts  
 Standards/Regulations  
 IEC 60269-2 fuse system A  
 DIN 43620  
 VDE 0636-2

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)  
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /  
 Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])  
 Construction size  
 NH000  
 Rated current  
 10 A  
 Rated voltage  
 690 V  
 Voltage type  
 AC  
 Rated switching capacity  
 120 kA  
 Utilization category  
 gL/gG (cable protection/equipment protection)  
 Type of fuse status indicator  
 Combination fuse status indicator  
 Insulated metal gripping lugs (IMGL)  
 No

## Product photo

- □ [100nhg000b\\_c](#)  
Photo
- 
- □ [100nhg000b\\_l](#)  
Photo
- □ [100nhg000b\\_r](#)  
Photo

-   
[10nhg000b-690\\_bk](#)  
Photo

-   
[10nhg000b-690\\_c](#)  
Photo

-   
[10nhg000b-690\\_r](#)  
Photo

-   
[10nhg000b-690\\_tp](#)  
Photo

# Declaration of Conformity

## EU

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00003483\)](#)  
Asset  
(PDF)

## UK

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004045\)](#)  
Asset  
(PDF)

# Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)  
© 2021 by Eaton Industries GmbH