

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 32A 500V GG/GL SIZE 01 - Fuse-link, low voltage, 32 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, live gripping lugs



32NHG01B NH FUSE 32A 500V GG/GL SIZE 01

[Overview](#) [Specifications](#) [Resources](#)



32NHG01B NH FUSE 32A 500V GG/GL SIZE 01

Fuse-link, low voltage, 32 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664039

Fuse, fuse-link, low voltage, 32 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•

•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
32 A
Rated voltage
AC 500 V
Construction size
NH01
Utilization category
gL/gG

Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
Other
Rated current
32 A
Rated voltage
500 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
gL/gG (cable protection/equipment protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo

- ☐ [32nhg01b_b](#)
Photo



- [32NHG01B_c](#)
Photo



- [32NHG01B_l](#)
Photo

- ☐ [32nhg01b_pkg](#)
Photo



- [32NHG01B_r](#)
Photo

Declaration of Conformity

EU

- [Size 01/1, 500V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00003487\)](#)
Asset
(PDF)

UK

- [Size 01/1, 500V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004029\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)
[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH