

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 25AMP 690V aM SIZE 000 - Fuse-link, low voltage, 25 A, AC 690 V, 120 kA, NH000, aM, IEC, dual indicator, live gripping lugs



25NHM000B-690 NH FUSE 25AMP 690V aM SIZE 000

[Overview](#) [Specifications](#) [Resources](#)



25NHM000B-690 NH FUSE 25AMP 690V aM SIZE 000

Fuse-link, low voltage, 25 A, AC 690 V, 120 kA, NH000, aM, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664138

Fuse, fuse-link, low voltage, 25 A, AC 690 V, NH000, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



•



•

Delivery program

•

Technical data ETIM 7.0

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
25 A
Rated voltage

AC 690 V
Construction size
NH000
Utilization category
aM
Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
NH000
Rated current
25 A
Rated voltage
690 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
aM (switchgear protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo



25nhm000b-690_b
Photo



25nhm000b-690_c
Photo



25nhm000b-690_l
Photo



25nhm000b-690_r

Photo

Declaration of Conformity

EU

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00003508\)](#)

Asset

(PDF)

UK

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00004040\)](#)

Asset

(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

