

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 40A 690V aM SIZE 000 - Fuse-link, low voltage, 40 A, AC 690 V, 120 kA, NH000, aM, IEC, dual indicator, live gripping lugs



40NHM000B-690 NH FUSE 40A 690V aM SIZE 000

[Overview](#) [Specifications](#) [Resources](#)



40NHM000B-690 NH FUSE 40A 690V aM SIZE 000

Fuse-link, low voltage, 40 A, AC 690 V, 120 kA, NH000, aM, IEC, dual indicator, live gripping lugs

EL-Nummer (Norway)

1664141

Fuse, fuse-link, low voltage, 40 A, AC 690 V, NH000, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



•



•

Delivery program

•

Technical data ETIM 7.0

Delivery program

Product range

Fuse

Basic function

Fuse-link

Field of application

low voltage

Rated current [I]

40 A

Rated voltage

AC 690 V
Construction size
NH000
Utilization category
aM
Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Low-Voltage HRC fuse (ec@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
NH000
Rated current
40 A
Rated voltage
690 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
aM (switchgear protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo





Declaration of Conformity

EU

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00003508\)](#)
Asset
(PDF)

UK

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00004040\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH

