

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 6AMP 690V SIZE 000 GG MGL - Fuse-link, low voltage, 6 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs



6NHG000B-690 NH FUSE 6AMP 690V SIZE 000 GG MGL

[Overview](#) [Specifications](#) [Resources](#)



6NHG000B-690 NH FUSE 6AMP 690V SIZE 000 GG MGL

Fuse-link, low voltage, 6 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664097

Fuse, fuse-link, low voltage, 6 A, AC 690 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



•



•



•



•



•

Delivery program

•

Technical data ETIM 7.0

Delivery program

Product range

Fuse
 Basic function
 Fuse-link
 Field of application
 low voltage
 Rated current [I]
 6 A
 Rated voltage
 AC 690 V
 Construction size
 NH000
 Utilization category
 gL/gG
 Status indicator
 dual indicator
 Description
 live gripping lugs
 Breaking Capacity
 120 kA
 usable for size/applications
 industrial
 Standard/Approval
 IEC
 Shape
 square body with knife blade contacts
 Standards/Regulations
 IEC 60269-2 fuse system A
 DIN 43620
 VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
 Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
 Construction size
 NH000
 Rated current
 6 A
 Rated voltage
 690 V
 Voltage type
 AC
 Rated switching capacity
 120 kA
 Utilization category
 gL/gG (cable protection/equipment protection)
 Type of fuse status indicator
 Combination fuse status indicator
 Insulated metal gripping lugs (IMGL)
 No

Product photo

- □ [100nhg000b_c](#)
Photo
- 
- □ [100nhg000b_l](#)
Photo
- □ [100nhg000b_r](#)
Photo

- 
[6nhg000b-690_bk](#)
Photo

- 
[6nhg000b-690_c](#)
Photo

- 
[6nhg000b-690_r](#)
Photo

- 
[6nhg000b-690_tp](#)
Photo

Declaration of Conformity

EU

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00003483\)](#)
Asset
(PDF)

UK

- [Size 000, 690V fuse-links with blade contacts \(NH fuse system\) \(DA-DC-00004045\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH