

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 35AMP 690V aM SIZE 000 - Fuse-link, low voltage, 35 A, AC 690 V, 120 kA, NH000, aM, IEC, dual indicator, live gripping lugs



35NHM000B-690 NH FUSE 35AMP 690V aM SIZE 000

[Overview](#) [Specifications](#) [Resources](#)



# 35NHM000B-690 NH FUSE 35AMP 690V aM SIZE 000

Fuse-link, low voltage, 35 A, AC 690 V, 120 kA, NH000, aM, IEC, dual indicator, live gripping lugs  
EL-Nummer (Norway) 1664140

Fuse, fuse-link, low voltage, 35 A, AC 690 V, NH000, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA



•



•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

## Delivery program

Product range  
Fuse  
Basic function  
Fuse-link  
Field of application  
low voltage  
Rated current [I]  
35 A  
Rated voltage

AC 690 V  
Construction size  
NH000  
Utilization category  
aM  
Status indicator  
dual indicator  
Description  
live gripping lugs  
Breaking Capacity  
120 kA  
usable for size/applications  
industrial  
Standard/Approval  
IEC  
Shape  
square body with knife blade contacts  
Standards/Regulations  
IEC 60269-2 fuse system A  
DIN 43620  
VDE 0636-2

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)  
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /  
Low-Voltage HRC fuse (ec@ss10.0.1-27-14-20-05 [AFZ800015])  
Construction size  
NH000  
Rated current  
35 A  
Rated voltage  
690 V  
Voltage type  
AC  
Rated switching capacity  
120 kA  
Utilization category  
aM (switchgear protection)  
Type of fuse status indicator  
Combination fuse status indicator  
Insulated metal gripping lugs (IMGL)  
No

## Product photo



•



50nhm000b-690\_r

Photo

## Declaration of Conformity

### EU

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00003508\)](#)  
Asset  
(PDF)

### UK

- [690V fuse-links with blade contacts \(NH fuse system\). Motor rated \(DA-DC-00004040\)](#)  
Asset  
(PDF)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

