

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NH FUSE 80AMP 690V aM SIZE 1 - Fuse-link, low voltage, 80 A, AC 690 V, 120 kA, NH1, aM, IEC, dual indicator, live gripping lugs



80NHM1B-690 NH FUSE 80AMP 690V aM SIZE 1

[Overview](#) [Specifications](#) [Resources](#)



80NHM1B-690 NH FUSE 80AMP 690V aM SIZE 1

Fuse-link, low voltage, 80 A, AC 690 V, 120 kA, NH1, aM, IEC, dual indicator, live gripping lugs

EL-Nummer (Norway)

0001664148

Fuse, fuse-link, low voltage, 80 A, AC 690 V, NH1, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2.

Breaking capacity 120 kA

•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range

Fuse

Basic function

Fuse-link

Field of application

low voltage

Rated current [I]

80 A

Rated voltage

AC 690 V

Construction size

NH1

Utilization category


aM

Status indicator
 dual indicator
 Description
 live gripping lugs
 Breaking Capacity
 120 kA
 usable for size/applications
 industrial
 Standard/Approval
 IEC
 Shape
 square body with knife blade contacts
 Standards/Regulations
 IEC 60269-2 fuse system A
 DIN 43620
 VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
 Low-Voltage HRC fuse (ec1@ss10.0.1-27-14-20-05 [AFZ800015])
 Construction size
 NH1
 Rated current
 80 A
 Rated voltage
 690 V
 Voltage type
 AC
 Rated switching capacity
 120 kA
 Utilization category
 aM (switchgear protection)
 Type of fuse status indicator
 Combination fuse status indicator
 Insulated metal gripping lugs (IMGL)
 No

Product photo





Declaration of Conformity

EU

- 690V fuse-links with blade contacts (NH fuse system). Motor rated (DA-DC-00003508)
Asset
(PDF)

UK

- 690V fuse-links with blade contacts (NH fuse system). Motor rated (DA-DC-00004040)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)
[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2021 by Eaton Industries GmbH