



Powering Business Worldwide



C22M40

CYLINDRICAL FUSE 22 x 58 40A AM 690V AC

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data ETIM7.0](#)

DELIVERY PROGRAM

Product range
Fuse

Basic function
Fuse-link

Field of application
low voltage

Rated current [I]
40 A

Rated voltage
AC 690 V

Size
22 x 58 mm

Utilization category
aM

Breaking Capacity
80 kA

usable for size/applications
motor protection
for industrial applications

Standard/Approval
IEC

Shape
cylindrical

Standards/Regulations
IEC 60269-2

TECHNICAL DATA ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])

Size
22x58 mm

Rated voltage
690 - 690 V

Rated voltage
Other

Voltage type
AC

Utilization category
aM (switchgear protection)

Rated operating frequency
45 - 62 Hz

Nominal current
40 A

With striker
No

Release characteristic
Other

Breaking capacity
80 kA

