

Select your language



- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NH FUSE 224AMP 690V gG SIZE 1 DUAL IND - Fuse-link, low voltage, 224 A, AC 690 V, 120 kA, NH1, gL/gG, IEC, dual indicator, live gripping lugs



224NHG1B-690 NH FUSE 224AMP 690V gG SIZE 1 DUAL IND

[Overview](#) [Specifications](#) [Resources](#)



224NHG1B-690 NH FUSE 224AMP 690V gG SIZE 1 DUAL IND

Fuse-link, low voltage, 224 A, AC 690 V, 120 kA, NH1, gL/gG, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664120

Fuse, fuse-link, low voltage, 224 A, AC 690 V, NH1, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
224 A
Rated voltage
AC 690 V
Construction size
NH1
Utilization category
gL/gG

Status indicator
dual indicator
Description
live gripping lugs
Breaking Capacity
120 kA
usable for size/applications
industrial
Standard/Approval
IEC
Shape
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Low-Voltage HRC fuse (ec1@ss10.0.1-27-14-20-05 [AFZ800015])
Construction size
NH1
Rated current
224 A
Rated voltage
690 V
Voltage type
AC
Rated switching capacity
120 kA
Utilization category
gL/gG (cable protection/equipment protection)
Type of fuse status indicator
Combination fuse status indicator
Insulated metal gripping lugs (IMGL)
No

Product photo

•



[224nhg1b-690_b](#)

Photo

•



[224NHG1B-690_c](#)

Photo

•



[224nhg1b-690_l](#)

Photo

•

[224nhg1b-690_pkg](#)

Photo

- 

[224NHG1B-690_r](#)

 Photo
- ☐

[250nhg1b-690_c](#)

 Photo
- ☐

[250nhg1b-690_l](#)

 Photo
- ☐

[250NHG1B-690_r](#)

 Photo

Declaration of Conformity

EU

- Size 1, 690V fuse-links with blade contacts (NH fuse system) (DA-DC-00003481)

 Asset

 (PDF)

UK

- Size 1, 690V fuse-links with blade contacts (NH fuse system) (DA-DC-00004049)

 Asset

 (PDF)

Download-Center

- [Download-Center \(this item\)](#)

 Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)

 Eaton EMEA Download-Center


[Generate data sheet in PDF format](#)


[Generate data sheet in Excel format](#)


[Write a comment](#)

[Imprint](#)
[Privacy Policy](#)
[Legal Disclaimer](#)
[Terms and Conditions](#)

 © 2021 by Eaton Industries GmbH
 