

- Worldwide English



Overview Specifications Resources



Fuse-link, low voltage, 450 A, AC 500 V, 120 kA, NH3, gL/gG, IEC, dual indicator, live gripping lugs
EL-Nummer (Norway) 1664086

Fuse, Fuse-link, low voltage, 450 A, AC 500 V, NH3, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

-



-



- Delivery program
- Technical data ETIM 7.0

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
450 A
Rated voltage
AC 500 V
Construction size
NH3
Utilization category
gL/gG

Status indicator
 dual indicator
 Description
 live gripping lugs
 Breaking Capacity
 120 kA
 usable for size/applications
 industrial
 Standard/Approval
 IEC
 Shape
 square body with knife blade contacts
 Standards/Regulations
 IEC 60269-2 fuse system A
 DIN 43620
 VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
 Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])
 Construction size
 NH3
 Rated current
 450 A
 Rated voltage
 500 V
 Voltage type
 AC
 Rated switching capacity
 120 kA
 Utilization category
 gL/gG (cable protection/equipment protection)
 Type of fuse status indicator
 Combination fuse status indicator
 Insulated metal gripping lugs (IMGL)
 No

Product photo



[500nhg3b_c](#)
 Photo



[500nhg3b_l](#)
 Photo



[500nhg3b_r](#)
 Photo

Download-Center

- [Download-Center \(this item\)](#)
 Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
 Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by [Eaton Industries GmbH](#)

