



6094964

DMM-125/3/M4/P-R

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

DELIVERY PROGRAM

Product range
Switch-disconnector
Main switch
maintenance switch

Part group reference
DMM

Stop Function
Emergency switching off function

With red rotary handle and yellow locking ring

Information about equipment supplied
auxiliary contact fitted by user.

Notes
With metal shaft for a control panel depth of 400 mm

Number of poles
3 pole


Auxiliary contacts


0 NO



0 NC

Degree of Protection
IP20

Design
rear mounting



Contact sequence



Motor rating AC-23A, 50 - 60 Hz [P]

400 V [P]
59 kW

Rated uninterrupted current [I_u]
125 A

Note on rated uninterrupted current I_u
Rated uninterrupted current I_u is specified for max.
cross-section.

TECHNICAL DATA

General

Standards
IEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3

Certifications
CE, RoHs, KEMA, EAC, Lloyds

Ambient temperature
Operation [9]
-25 - +60 °C

Ambient temperature
Storage [9]
-40 - +80 °C

Overvoltage category/pollution degree
III/3

Rated impulse withstand voltage [U_{imp}]
6 kV

Rated insulation voltage [U_i]
1000 V

Mounting position
As required

Contacts

Mechanical variables
Number of poles
3 pole

Mechanical variables
Auxiliary contacts

0 NO

Mechanical variables
Auxiliary contacts

0 NC

Electrical characteristics
Rated operational voltage [U_e]

690 V AC

Electrical characteristics

Rated uninterrupted current [I_u]

125 A

Electrical characteristics

Note on rated uninterrupted current I_u

Rated uninterrupted current I_u is specified for max. cross-section.

Short-circuit rating

fuse

125

Short-circuit rating

Rated conditional short-circuit current [I_q]

415 V: 30

690 V: 50 kA

Short-circuit rating

Breaking current

13.7 kA

Short-circuit rating

max. let-through energy

134 kA²s

Rated short-time withstand current (1 s current)

[I_{cw}]

2500 A_{rms}

Note on rated short-time withstand current I_{cw}

Current for a time of 1 second

Heat dissipation per pole, current-dependent [P_{id}]

4.9 W

Switching capacity

Rated breaking capacity $\cos \phi$ to IEC 60947-3

400/415 V

1000 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3

500 V

528 A

Rated breaking capacity $\cos \phi$ to IEC 60947-3
690 V
336 A

Safe isolation to EN 61140
Current heat loss per contact at I_e
4.5 W

Lifespan, mechanical [Operations]
10000

AC
AC-21A
Rated operational current switch
400 V 415 V [I_e]
125 A

AC
AC-21A
Rated operational current switch
500 V [I_e]
125 A

AC
AC-21A
Rated operational current switch
690 V [I_e]
125 A

AC
AC-22A
Rated operational current switch
400 V 415 V [I_e]
125 A

AC
AC-22A
Rated operational current switch
500 V [I_e]
125 A

AC
AC-22A
Rated operational current switch
690 V [I_e]
125 A

AC
AC-23A

Rated operational current switch
400 V 415 V [I_e]
125 A

AC
AC-23A
Rated operational current switch
500 V [I_e]
66 A

AC
AC-23A
Rated operational current switch
690 V [I_e]
42 A

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
400 V 415 V [P]
59 kW

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
500 V [P]
45 kW

AC
AC-23A
Motor rating AC-23A, 50 - 60 Hz [P]
690 V [P]
37 kW

Terminal capacities

Flexible with ferrules to DIN 46228
flexible
6 - 70 mm²

Stripping length
21 mm

Tightening torque for terminal screw
7 Nm

Technical safety parameters:

Notes

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_r]
125 A

Heat dissipation per pole, current-dependent [P_{id}]
4.9 W

Equipment heat dissipation, current-dependent [P_{id}]
0 W

Static heat dissipation, non-current-dependent [P_{is}]
0 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+40 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ec1@ss10.0.1-27-37-14-03 [AKF060013])

Version as main switch
Yes

Version as maintenance-/service switch
Yes

Version as safety switch
Yes

Version as emergency stop installation
Yes

Version as reversing switch
No

Number of switches
1

Max. rated operation voltage U_e AC
690 V

Rated operating voltage
690 - 690 V

Rated permanent current I_u
125 A

Rated permanent current at AC-23, 400 V
125 A

Rated permanent current at AC-21, 400 V
125 A

Rated operation power at AC-3, 400 V
0 kW

Rated short-time withstand current I_{cw}
2.5 kA

Rated operation power at AC-23, 400 V
59 kW

Switching power at 400 V
0 kW

Conditioned rated short-circuit current I_q
50 kA

Number of poles

3

Number of auxiliary contacts as normally closed
contact

0

Number of auxiliary contacts as normally open
contact

0

Number of auxiliary contacts as change-over
contact

0

Motor drive optional

No

Motor drive integrated

No

Voltage release optional

No

Device construction

Built-in device fixed built-in technique

Suitable for ground mounting

Yes

Suitable for front mounting 4-hole

No

Suitable for front mounting centre

No

Suitable for distribution board installation

Yes

Suitable for intermediate mounting

No

Colour control element

Red

Type of control element
Toggle

Interlockable
Yes

Type of electrical connection of main circuit
Screw connection

Degree of protection (IP), front side
IP20

Degree of protection (NEMA)
Other



