

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



FUSE 100A DIV 500VAC - Fuse-link, low voltage, 100 A, AC 500 V, 50 kA, D4, gR, IEC, fast-acting



100D125Q FUSE 100A DIV 500VAC

[Overview](#) [Specifications](#) [Resources](#)



100D125Q FUSE 100A DIV 500VAC

Fuse-link, low voltage, 100 A, AC 500 V, 50 kA, D4, gR, IEC, fast-acting

EL-Nummer (Norway) 1601252

Fuse, Fuse-link, low voltage, 100 A, AC 500 V, D4, gR, IEC, fast acting, bottle, for fuse-base R1, IEC 60269-3, VDE 0636, Breaking Capacity 50 kA



•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range

Fuse

Basic function

Fuse-link

Field of application

low voltage

Rated current [I]

100 A

Rated voltage

AC 500 V

Construction size

D4

Utilization category

gR

Breaking Capacity
50 kA
usable for size/applications
for fuse-base R1
Release characteristic [class]
fast-acting
Standard/Approval
IEC
Shape
bottle
Standards/Regulations
IEC 60269-3
VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])
Construction size
DIV
Rated current
100 A
Rated voltage
500 V
Colour code
Red
Utilization category
gR (general purpose semiconductor protection)
Release characteristic
Fast (F)

Product photo



Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

