

- Worldwide English

[Overview](#) [Specifications](#) [Resources](#)

E-Nummer (Norway)

1601261

Fuse, Fuse-link, low voltage, 16 A, AC 500 V, D1, gR, IEC, fast acting, bottle, E16, IEC 60269-3, VDE 0636, Breaking Capacity 50 kA



- Delivery program
- Technical data ETIM 7.0

Product range
Fuse
Basic function
Fuse-link
Rated current [I]
16 A
Rated voltage
AC 500 V
Construction size
D1
Size
13.2 x 6 mm
Utilization category
gR

Breaking Capacity
50 kA
usable for size/applications
E16
Release characteristic [class]
fast-acting
Standard/Approval
IEC
Shape
bottle
Standards/Regulations
IEC 60269-3
VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])
Construction size
DI
Rated current
16 A
Rated voltage
500 V
Colour code
Grey
Utilization category
gR (general purpose semiconductor protection)
Release characteristic
Fast (F)

Product photo



Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

