

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



FUSE-D3 40A T GL/GG 500VAC E33 - Fuse-link, low voltage, 40 A, AC 500 V, 50 kA, D3, gL/gG, DIN, IEC, time-delay



40D33 FUSE-D3 40A T GL/GG 500VAC E33

[Overview](#) [Specifications](#) [Resources](#)



40D33 FUSE-D3 40A T GL/GG 500VAC E33



Fuse-link, low voltage, 40 A, AC 500 V, 50 kA, D3, gL/gG, DIN, IEC, time-delay

EL-Nummer (Norway) 1601273

Fuse, Fuse-link, low voltage, 40 A, AC 500 V, D3, gL/gG, DIN, IEC, time-delay, bottle, E33, IEC 60269-3, VDE 0636, Breaking Capacity 50 kA

•



•



•



• [Delivery program](#)

• [Technical data ETIM 7.0](#)

Delivery program

Product range

Fuse

Basic function

Fuse-link

Field of application

low voltage

Rated current [I]

40 A

Rated voltage

AC 500 V
Construction size
D3
Utilization category
gL/gG
Breaking Capacity
50 kA
usable for size/applications
E33
Release characteristic [class]
time-delay
Standard/Approval
DIN
IEC
Shape
bottle
Standards/Regulations
IEC 60269-3
VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])
Construction size
DIII
Rated current
40 A
Rated voltage
500 V
Colour code
Black
Utilization category
gL/gG (cable protection/equipment protection)
Release characteristic
Time-lag

Product photo



40d33_b
Photo



40d33_c
Photo



40d33_l
Photo



40d33_r
Photo

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

