

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



FUSE 80A DIV 500VAC - Fuse-link, low voltage, 80 A, AC 500 V, 50 kA, D4, gR, DIN, IEC, fast-acting



80D125Q FUSE 80A DIV 500VAC

[Overview](#) [Specifications](#) [Resources](#)



80D125Q FUSE 80A DIV 500VAC

Fuse-link, low voltage, 80 A, AC 500 V, 50 kA, D4, gR, DIN, IEC, fast-acting

EL-Nummer (Norway) 1601281

Fuse, Fuse-link, low voltage, 80 A, AC 500 V, D4, gR, DIN, IEC, fast-acting, bottle, for fuse-base R1, IEC 60269-3, VDE 0636, Breaking Capacity 50 kA



- Delivery program
- Technical data ETIM 7.0

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
80 A
Rated voltage

AC 500 V
Construction size
D4
Utilization category
gR
Breaking Capacity
50 kA
usable for size/applications
for fuse-base R1
Release characteristic [class]
fast-acting
Standard/Approval
DIN
IEC
Shape
bottle
Standards/Regulations
IEC 60269-3
VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])
Construction size
DIN
Rated current
80 A
Rated voltage
500 V
Colour code
Silver
Utilization category
gR (general purpose semiconductor protection)
Release characteristic
Fast (F)

Product photo



[80d125q_b](#)

Photo



[80d125q_c](#)

Photo



[80d125q_l](#)

Photo



[80d125q_r](#)

Photo

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

