

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



FUSE 10A D/E16 500VAC DZ - Fuse-link, 10 A, AC 500 V, 50 kA, D1, 13.2 x 6 mm, gR, IEC, fast-acting



10D16Q FUSE 10A D/E16 500VAC DZ

[Overview](#) [Specifications](#) [Resources](#)



10D16Q FUSE 10A DI/E16 500VAC DZ



Fuse-link, 10 A, AC 500 V, 50 kA, D1, 13.2 x 6 mm, gR, IEC, fast-acting

EL-Nummer (Norway)

1601254

Fuse, Fuse-link, low voltage, 10 A, AC 500 V, D1, 13.2 x 6 mm, gR, IEC, fast-acting, bottle, E16, for domestic and general industrial applications, IEC 60269-3, VDE 0636, Breaking Capacity 50 kA



- [Delivery program](#)
- [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Rated current [I]
10 A
Rated voltage
AC 500 V
Construction size
D1
Size
13.2 x 6 mm
Utilization category
gR

Breaking Capacity
50 kA
usable for size/applications
E16
for domestic and general industrial applications
Release characteristic [class]
fast-acting
Standard/Approval
IEC
Shape
bottle
Standards/Regulations
IEC 60269-3
VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])
Construction size
DI
Rated current
10 A
Rated voltage
500 V
Colour code
Red
Utilization category
gR (general purpose semiconductor protection)
Release characteristic
Fast (F)

Product photo



Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

