

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



FUSE-D4 100A T GL/GG 500VAC - Fuse-link, low voltage, 100 A, AC 500 V, 50 kA, D4, gL/gG, IEC, time-delay



100D125 FUSE-D4 100A T GL/GG 500VAC

[Overview](#) [Specifications](#) [Resources](#)



100D125 FUSE-D4 100A T GL/GG 500VAC

Fuse-link, low voltage, 100 A, AC 500 V, 50 kA, D4, gL/gG, IEC, time-delay

EL-Nummer (Norway)

1601251

Fuse, fuse-link, low voltage, 100 A, AC 500 V, D4, gL/gG, IEC, time-delay, for domestic and general industrial applications, for general purpose use, for industrial applications, for motor control transformers and circuits with in-rush currents, ground fault protection, ideal for critical industrial or commercial applications that have specific current limitation requirements, motor overload protection, motor protection, short-circuit protection, IEC 60269-3, VDE 0636



- [Delivery program](#)
- [Technical data ETIM 7.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link

Field of application
 low voltage
 Rated current [I]
 100 A
 Rated voltage
 AC 500 V
 Construction size
 D4
 Utilization category
 gL/gG
 Breaking Capacity
 50 kA
 usable for size/applications
 for domestic and general industrial applications
 for general purpose use
 for industrial applications
 for motor control transformers and circuits with in-rush currents
 ground fault protection
 ideal for critical industrial or commercial applications that have specific current limitation requirements
 motor overload protection
 motor protection
 short-circuit protection
 Release characteristic [class]
 time-delay
 Standard/Approval
 IEC
 Shape
 bottle
 Standards/Regulations
 IEC 60269-3
 VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)
 Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
 Diazed fuse link (ecl@ss 10.0.1-27-14-20-04 [AFZ799015])
 Construction size
 DIV
 Rated current
 100 A
 Rated voltage
 500 V
 Colour code
 Red
 Utilization category
 gL/gG (cable protection/equipment protection)
 Release characteristic
 Time-lag

Product photo



[100d125_b](#)
 Photo



[100d125_c](#)
 Photo



[100d125_I](#)

Photo



[100d125_pkg](#)

Photo



[100d125_r](#)

Photo

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

