

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



XNH3-FCL-A630-BT - NH fuse-switch 3p box terminal 95 - 300 mm²; mounting plate; light fuse monitoring; NH3



183074 XNH3-FCL-A630-BT

[Overview](#) [Specifications](#) [Resources](#)



183074 XNH3-FCL-A630-BT

NH fuse-switch 3p box terminal 95 - 300 mm²; mounting plate; light fuse monitoring; NH3
EL-Nummer (Norway) 1624049

NH fuse switch-disconnector 3 pole with box terminal 95 - 300 mm²; mounting plate; light fuse monitoring with LED; for NH3 fuse-links; optionally lockable with XNH-XLOCK and padlock



• [Delivery program](#)

• [Technical data](#)

• [Design verification as per IEC/EN 61439](#)

Delivery program

Basic function
Fuse control - light
Number of poles
3 pole

- Technical data ETIM 7.0
- Dimensions

Mounting type
 DIN rails
 Mounting plate
 Size
 3
 Type of connection
 Box terminal
 Rated operational current [I_n]
 630 A
 Front degree of protection (XNH installed)
 IP20 (Operating status)
 IP2XC (Contact protection)
 IP10 (Handle cover open)
 Rated operational voltage [U_n]
 690 V AC
 Rated operational voltage [U_n]
 440 V DC
 Rated conditional short-circuit current
 120 (500 V)
 100 (690 V) kA
 Flammability characteristics
 Self-extinguishing as per UL 94
 Description
 Current paths of electrolytic copper, silver-plated
 With optical signalling of triggered fuse-links

Technical data

Electrical
 Standards
 IEC/EN 60947-3
 Rated operational voltage [U_n]
 690 V AC
 Rated operational voltage [U_n]
 440 V DC
 Rated operational current [I_n]
 630 A
 Rated frequency [f]
 40 - 60 Hz
 Rated insulation voltage [U_i]
 800 V AC
 Total heat dissipation at I_{th} (without fuses) [P_d]
 51 W
 Heat dissipation at 80% (without fuses) [P_d]
 32.5 W
 Rated impulse withstand voltage [U_{imp}]
 8 kV
 Utilization category AC-23B Rated operating voltage [U_n]
 400 V AC
 Utilization category AC-23B Rated operating current [I_n]
 630 A
 Utilization category AC22B Rated operating voltage [U_n]
 500 V AC
 Utilization category AC22B Rated operating current [I_n]
 630 A
 Utilization category AC-21B Rated operating voltage [U_n]
 690 V AC
 Utilization category AC-21B Rated operating current [I_n]
 630 A
 Utilization category DC-22B Rated operating voltage [U_n]
 440 V DC
 Utilization category DC-22B Rated operating current [I_n]
 630 A
 Utilization category DC21B Rated operating voltage [U_n]
 250 V DC
 Utilization category DC21B Rated operating current [I_n]
 630 A
 Rated conditional short-circuit current
 120 (500 V)

100 (690 V) kA
 Rated short-time withstand current [I_{cw}]
 10 kA
 Max. fuseSize according to DIN VDE 0636-2
 3 / 2
 Max. fuseMax. permitted power loss per fuse link [P_d]
 48 W
 Lifespan, electrical [Operations]
 200
 Mechanical
 Front degree of protection (XNH installed)
 IP20 (Operating status)
 IP2XC (Contact protection)
 IP10 (Handle cover open)
 Ambient temperature
 -25 - +55 °C
 Rated operating mode
 Permanent operation
 Activation
 Dependent manual activation
 Mounting position
 Vertical, horizontal
 Altitude
 Max. 2000 m
 Overvoltage category/pollution degree
 III/3
 RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)
 Yes
 Direction of incoming supply
 as required
 Lockable
 Yes, optional
 Sealable
 Yes, Standard
 Material characteristicsMaterial
 Polyamide
 Material characteristicsColour
 Grey
 Flammability characteristics
 Self-extinguishing as per UL 94
 Halogen-free
 Yes
 Voltage test
 Yes, sliding inspection windows
 Lifespan, mechanical [Operations]
 800
 Track resistance
 CTI 600
 Heat deflection temperature
 125 °C
 Terminal capacity
 Flange connectionBolt diameter
 M10
 Flange connectionCable lug max. width
 56 mm
 Flange connectionFlat busbar
 50 x 10 mm
 Box terminalStranded
 95 - 300 Cu/Al mm²
 Box terminalCopper strip [Number of segments x width x thickness]
 6 x 16 x 0,8 - 10 x 32 x 1 mm
 Box terminalStranded
 auf Anfrage mm²
 Box terminalCopper band [Number of segments x width x thickness]
 11 x 21 x 1 mm
 Clamp-type terminalStranded
 120 - 300 Cu/Al mm²
 Double clamp-type terminalStranded
 2x (120 - 240) Cu/Al mm²

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

630 A

Heat dissipation per pole, current-dependent [P_{vd}]

7.3 W

Equipment heat dissipation, current-dependent [P_{vd}]

22 W

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

$U_i = 800$ V AC

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ec1@ss10.0.1-27-37-14-01 [AKF058013])

Version as main switch

No

Version as safety switch

No

Max. rated operation voltage U_e AC

690 V

Rated permanent current I_n

630 A

Rated operation power at AC-23, 400 V

0 kW
Conditioned rated short-circuit current I_q
120 kA
Rated short-time withstand current I_{cw}
3 kA
Suitable for fuses
NH3
Number of poles
3
With error protection
Yes
Type of electrical connection of main circuit
Frame clamp
Cable entry
Other
Equipped with connectors
No
Suitable for ground mounting
Yes
Suitable for front mounting 4-hole
No
Suitable for busbar mounting
No
Type of control element
Cover grip
Position control element
Front side
Motor drive optional
No
Motor drive integrated
No
Version as emergency stop installation
No
Degree of protection (IP), front side
Other

Dimensions

Product photo



vt00516
Photo
3-pole fuse switch-disconnector, box terminals



vt03716
Photo
Fuse switch-disconnectors



vt58715
Photo
Fuse switch-disconnectors



[vt65115](#)

Photo

Fuse switch-disconnectors



[wa_vt14515](#)

Photo

Fuse switch-disconnectors

Dimensions single product

-  [1230DIM-357](#)
Line drawing

Instruction Leaflet

- [IL0131110ZU](#)
Asset
(PDF, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

