



Terminal block, 1 pole, 800A, 2 output terminals, ALU

Part no. **BPZ-KB-1/2/800-ALU**
 Catalog No. **102712**

EL-Nummer
 (Norway) **1243569**

Delivery program

Mounting type			Floor standing distribution board Surface mounted Flush mounted
Material			Aluminium
Degree of Protection			IP10
Mounting position			universal
Number of poles			1 pole
Width		mm	72
Depth		mm	80
Height		mm	145
Number of clamping units per pole			3
Rated device current		A	800

Technical data

General

Standards			IEC 60 947 -7 -1
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Heat deflection temperature		°C	100
UL 94 flame classification			V-0
Comparative tracking index		V	600
Degree of Protection			IP10
Assembly details			Clicks on DIN-rail or on base plate. Save time on wiring. Save 80% on space used. Modular construction, 1-4 pole Systems can be built with several blocks.
Important			This Power Distribution Block is suitable for ALU and CU conductors. Please pay attention to the common handling guidelines when connecting the Aluminium conductors. Clean and brush the contact surfaces and lubricate them with an appropriate grease. As precaution the connections should get retightened regularly.

Electrical

IEC			
Max. electrical load / Al		A	630
Max. electrical load / Cu		A	800
Max. operating voltage / Al		V AC	1000
Max. operating voltage / Al		V DC	1500
Max. operating voltage / Cu		V AC	1000
Max. operating voltage / Cu		V DC	1500

Material characteristics

Material			
Clamping body			Aluminium
Housing			PA66
Hexagon socket set screw			Steel
Surface finish			
Clamping body			Plated
Hexagon socket set screw			Zn-Plated
Colour			
Housing			grey, RAL 7035

Terminal capacity

Incomer			
---------	--	--	--

single wire/multi wire		mm ²	35 - 300
single wire/multi wire		AWG	2 - 600 MCM
fine wire (with sleeve)		mm ²	16 - 240
fine wire (with sleeve)		AWG	6 - 500 MCM
Flat copper bars			9 x 4 - 50 x 10
Torque		N/m	25 - 35
Torque		lbf	221 - 309.7
Outgoings			
single wire/multi wire		mm ²	35 - 300
fine wire (with sleeve)		mm ²	16 - 240
Flat copper bars		mm	9 x 4 - 24 x 10
Torque		N/m	25 - 35
Torque		lbf	221 - 309.7
Notes regarding connection			Al-sector conductors tested up to 70mm ²

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Distributor assembly terminal blocks (EC001894)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Distributor assembly terminal blocks (ecI@ss10.0.1-27-40-06-09 [AC0381011])			
Height		mm	145
Width		mm	72
Depth		mm	80.5
Max. rated current		A	800
Number of poles			1
Conductor cross section flexible (fine-strand) with cable end sleeve		mm ²	35 - 300
Conductor cross section solid (solid, stranded)		mm ²	35 - 300
Number of clamp positions per pole			3
With PE-rail			No
With N-rail			No

Dimensions

