



Surface-mount service distribution board with three-point turn-lock, W = 800 mm, H = 1260 mm

Part no. BP-O-800/12
Article no. 100970

Delivery program

Mounting type			Surface mounted
Material			Sheet steel
Door interlock			Three-point turn-lock
Installation site			Indoor
Degree of Protection			IP30
Surface finish			With powder coating
Width		mm	800
Depth		mm	262
Height		mm	1260
Colour			light gray (RAL 7035)

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees, calculated as per IEC 60890			
Individual enclosure for wall mounting	P _V	CO	120
Starting enclosure for wall mounting	P _V	CO	108
Middle enclosure for wall mounting	P _V	CO	100
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees, calculated as per IEC 60890			
Individual enclosure for wall mounting	P _V	CO	240
Starting enclosure for wall mounting	P _V	CO	216
Middle enclosure for wall mounting	P _V	CO	200
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			
Meets the product standard's requirements.			
10.2.3.1 Verification of thermal stability of enclosures			
Meets the product standard's requirements.			
10.2.3.2 Verification of resistance of insulating materials to normal heat			
Meets the product standard's requirements.			
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			
Meets the product standard's requirements.			
10.2.4 Resistance to ultra-violet (UV) radiation			
Not relevant to indoor installations.			
10.2.5 Lifting			
Does not apply to enclosures without lifting aids.			
10.2.6 Mechanical impact			
IK07			
10.2.7 Inscriptions			
Meets the product standard's requirements.			
10.3 Degree of protection of ASSEMBLIES			
IP30			
10.4 Clearances and creepage distances			
Is the panel builder's responsibility.			
10.5 Protection against electric shock			
< 0.1 Ω; meets the product standard's requirements.			
10.6 Incorporation of switching devices and components			
Is the panel builder's responsibility.			
10.7 Internal electrical circuits and connections			
Is the panel builder's responsibility.			
10.8 Connections for external conductors			
Is the panel builder's responsibility.			
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			
U _i = 440 V AC			
10.9.3 Impulse withstand voltage			
4 kV			
10.9.4 Testing of enclosures made of insulating material			
Does not apply to metal enclosures.			
10.10 Temperature rise			
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.			
10.11 Short-circuit rating			
Is the panel builder's responsibility.			
10.12 Electromagnetic compatibility			
Is the panel builder's responsibility.			
10.13 Mechanical function			
Meets the product standard's requirements.			

Technical data ETIM 6.0

Distribution boards (EG000023) / Small distribution board (EC000214)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Small distribution board
(ecI@ss8.1-27-14-24-09 [ACN387008])

Mounting method			Surface mounting
Number of rows			9
Width in number of modular spacings			35
Type of cover			Door
Cover model			Closed
Transparent cover/door			No
Material housing			Steel
Height		mm	1260
Width		mm	800
Depth		mm	262.5
Built-in depth		mm	0
Internal depth		mm	257.5
DIN-rail			Yes
With mounting plate			No
Extension possible			Yes
EMC-version			No
Colour			Grey
RAL-number			7035
Degree of protection (IP)			IP30
With lock			No