

Floor standing distribution board, flexible surface mounting, $W=800\ mm$, $H=1760\ mm$, $D=300\ mm$

Powering Business Worldwide

Part no. BP-F-800/17/3-F Article no. 102399

Delivery program

Mounting type		Floor standing distribution board
Material		Sheet steel
Installation site		Indoor
Degree of Protection		IP30
Surface finish		With powder coating
Width	mı	mm 800
Depth	mı	mm 300
Height	mı	mm 1760
Colour		light gray (RAL 7035)

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees, calculated as per IEC 60890			
Individual enclosure, free-standing	P_{V}	CO	193
Starting enclosure, free-standing	P_{V}	CO	189
Middle enclosure, free-standing	P_{V}	CO	187
Individual enclosure for wall mounting	P_{V}	CO	173
Starting enclosure for wall mounting	P_{V}	CO	159
Middle enclosure for wall mounting	P_{V}	CO	149
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees, calculated as per IEC 60890			
Individual enclosure, free-standing	P_{V}	CO	388
Starting enclosure, free-standing	P_{V}	CO	379
Middle enclosure, free-standing	P_{V}	CO	374
Individual enclosure for wall mounting	P_{V}	CO	347
Starting enclosure for wall mounting	P_{V}	CO	320
Middle enclosure for wall mounting	P_{V}	CO	298
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 Mechanical impact			IK07
10.2.7 Inscriptions			Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES	IP30
10.4 Clearances and creepage distances	Is the panel builder's responsibility.
10.5 Protection against electric shock	$<$ 0.1 $\Omega;$ meets the product standard's requirements.
10.6 Incorporation of switching devices and components	Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9 Insulation properties	
10.9.2 Power-frequency electric strength	U _i = 440 V AC
10.9.3 Impulse withstand voltage	4 kV
10.9.4 Testing of enclosures made of insulating material	Does not apply to metal enclosures.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	Meets the product standard's requirements.

Technical data ETIM 6.0

I Common uata E i nvi 0.0					
Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)					
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss8.1-27-18-01-01 [AGZ056013])					
Width	mm 800				
Height	mm 1760				
Depth	mm 300				
Material	Steel				
Type of surface	With powder coating				
Colour	Grey				
RAL-number	7035				
With mounting plate	No				
Mounting plate depth-adjustable	Yes				
Number of locks	0				
Floor installation possible	Yes				
Wall fastening possible	No				
Wall build in	No				
Pole fastening	No				
Tackable	Yes				
Number of doors	0				
Suitable for metrical mounting	Yes				
Suitable for outdoor set-up	No				
Pitched roof	No				
EMC-version	Yes				
Impact strength	IK07				
Degree of protection (IP)	IP30				
With glazed door	No				
With ventilation door	No				
With backside door	No				