

Door, metal, for HxW = 2060 x 800 mm

Part no. **BPZ-DS-800/20**
Article no. **102424**



Delivery program

| | | | |
|----------------------|--|----|-----------------------------------------------------------------------|
| Mounting type | | | Floor standing distribution board Surface mounted Flush mounted |
| Material | | | Sheet steel |
| Door interlock | | | Three-point turn-lock |
| Degree of Protection | | | IP30 |
| Surface finish | | | With powder coating |
| Width | | mm | 800 |
| Height | | mm | 2060 |
| Suitable for height | | mm | 2060 |
| Suitable for width | | mm | 800 |
| Colour | | | light gray (RAL 7035) |

Technical data ETIM 6.0

| | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|---------------------|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecI@ss8.1-27-18-22-04 [ACN614008]) | | | |
| Model | | | Stop door |
| Version as glazed door | | | No |
| Version as door for disconnecting switch interlocking | | | No |
| Width | | mm | 792 |
| Height | | mm | 1996.5 |
| Depth | | mm | 35 |
| EMC-version | | | No |
| Material | | | Steel |
| Type of surface | | | With powder coating |
| Colour | | | Grey |
| Degree of protection (IP) | | | IP30 |