

Metal door, for HxW=2060x600mm, left

Part no. BPZ-DS-600/20-L Article no. 106377



Delivery program

Basic function Product function Accessories Doors Single unit/Complete unit Description Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Material Surface finish Unformation about equipment supplied Can be used as right door for two-leaf versions order together with standard door for 600 mm Protection type Suitable for width Floor-standing enclosures Accessories Accessories Doors Mounting enclosures Modular system Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock With powder coating Floor-standing enclosures Modular system Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Sheet steel Surface finish Floor-standing enclosures Floor-standing enclosures Floor-standing enclosures Mounting enclosures Floor-standing enclosures Mounting enclosures Floor-standing enclosures Floor-standi		
Product function Accessories Accessories Doors Single unit/Complete unit Modular system Description Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Material Sheet steel Surface finish With powder coating Information about equipment supplied can be used as right door for two-leaf versions order together with standard door for 600 mm Protection type IP30 Suitable for width 1200 Suitable for height 2060	Product range	Service distribution board IVS
Accessories Single unit/Complete unit Description Desc	Basic function	Floor-standing enclosures
Single unit/Complete unit Description Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Material Surface finish With powder coating Information about equipment supplied Protection type Suitable for width Suitable for height Modular system Modular system Modular system Modular system Modular system Modular system And Information system With powder Sheet steel With powder coating can be used as right door for two-leaf versions order together with standard door for 600 mm 1200 Suitable for height	Product function	Accessories
Description Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Material Surface finish With powder coating Information about equipment supplied can be used as right door for two-leaf versions order together with standard door for 600 mm Protection type IP30 Suitable for width 1200 Suitable for height 2060	Accessories	Doors
Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Material Sheet steel Surface finish With powder coating Information about equipment supplied can be used as right door for two-leaf versions order together with standard door for 600 mm Protection type IP30 Suitable for width 200 Suitable for height Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Sheet steel With powder coating can be used as right door for two-leaf versions order together with standard door for 600 mm 1200 Suitable for height	Single unit/Complete unit	Modular system
Surface finish Information about equipment supplied Protection type Suitable for height With powder coating can be used as right door for two-leaf versions order together with standard door for 600 mm IP30 Suitable for height 2060	Description	Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167°
Information about equipment supplied can be used as right door for two-leaf versions order together with standard door for 600 mm Protection type IP30 Suitable for width 1200 Suitable for height 2060	Material	Sheet steel
order together with standard door for 600 mm Protection type Suitable for width 1200 Suitable for height 2060	Surface finish	With powder coating
Suitable for height 1200 2060	Information about equipment supplied	
Suitable for height 2060	Protection type	IP30
	Suitable for width	1200
Protective cover mounted on left	Suitable for height	2060
		Protective cover mounted on left
		Trocodive dover modification of force

Notes

Two-section doors are used from width 1000 mm, order the right and left doors separately.