

3-component flush-mounted door frame with door, open air, rotary lever, IP43, HxW=1260x1200mm



Part no. BPA-U-3S-1200/12-P Article no. 119145

| D | | | |
|----------|--------|-------|------|
| 110 | INCE | INFO | arom |
| UH | IIVEIV | / WIU | gram |
| | | | |

| Mounting type | | Flush mounted |
|----------------------|----|-----------------------|
| Features | | with door |
| Features | | with door |
| Material | | Aluminium |
| Door interlock | | Rotary lever |
| Installation site | | Outdoor |
| Degree of Protection | | IP43 |
| Surface finish | | With powder coating |
| Suitable for width | mm | 1200 |
| Colour | | light gray (RAL 7035) |

Technical data ETIM 6.0

| Technical data Etilyi 6.0 | | | | | |
|--|-----------------|-----------|--|--|--|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000 | 747) | | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, [ACN614008]) | housing, rack / | Door (ele | ctrical cabinet) / Door/operating panel (enclosure) (ecl@ss8.1-27-18-22-04 | | |
| Model | | | Stop door | | |
| Version as glazed door | | | No | | |
| Version as door for disconnecting switch interlocking | | | No | | |
| Width | | mm | 1235 | | |
| Height | | mm | 1260 | | |
| Depth | | mm | 85 | | |
| EMC-version | | | No | | |
| Material | | | Aluminium | | |
| Type of surface | | | With powder coating | | |
| Colour | | | Grey | | |
| Degree of protection (IP) | | | IP43 | | |