



Cable gland, M12, RAL 7035, IP68_x

Part no. **V-M12**
Article no. **215078**

Delivery program

Product range			General switchboard accessories
Accessories			Cable management
Cable entry			M12
Hole diameter		mm	12,5
Outer cable diameter		mm	3 - 7
Example of application: NYM/NYY cable, 4-core		mm ²	H03VV-F3 x 0.75, NYM 1 x 2.5
Description			Flammability classification V2 according to UL94 With lock nut and built-in strain relief
Material			Polyamide Halogen free
Surface finish			RAL 7035
Information about equipment supplied			With lock nut and built-in strain relief
Degree of Protection			IP68 up to 5 bar (30 min)
Notes <title>Cable glands, ventilation cable glands, cable grommet</title>			
→ See chapter 16, Accessories for control panel building			

Technical data

General

Degree of Protection			IP68 up to 5 bar (30 min)
----------------------	--	--	---------------------------

Material characteristics

Material			Polyamide Halogen free
Colour			Gray, RAL 7035
Temperature resistant			-20 °C - 100 °C, short-time up to approx. 120 °C
Chemical resistant			Resistant against : Acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishes
Danger of stress fracture			low
Flame retardant			Glow wire test 750 °C according to EN 60695-2-11
Flammability classification according to UL94			V2

Dimensions



