

3-component flush-mounting door frame with door, open air, double-bit lock, IP43, HxW=2060x800mm $\,$



Part no. BPA-U-3S-800/20 Article no. 111235

Delivery program

| Mounting type | | Flush mounted |
|----------------------|----|-----------------------|
| Features | | with door |
| Features | | with door |
| Material | | Aluminium |
| Door interlock | | Double-ward lock |
| Installation site | | Outdoor |
| Degree of Protection | | IP43 |
| Surface finish | | With powder coating |
| Suitable for width | mm | 800 |
| Colour | | light gray (RAL 7035) |

| Technical data ETIM 6.0 | | | | |
|--|----|---------------------|--|--|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747) | | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss8.1-27-18-22-04 [ACN614008]) | | | | |
| Model | | Stop door | | |
| Version as glazed door | | No | | |
| Version as door for disconnecting switch interlocking | | No | | |
| Width | mm | 835 | | |
| Height | mm | 2060 | | |
| Depth | mm | 85 | | |
| EMC-version | | No | | |
| Material | | Aluminium | | |
| Type of surface | | With powder coating | | |
| Colour | | Grey | | |
| Degree of protection (IP) | | IP43 | | |