

Sheet steel door transparent with rotary door handle for IVS HxW=510x600mm



Part no. BP-DT-600/4.5 Article no. 111354

Delivery program

Resisce function Recessories R	71 0		
Accessories Doors Single unit/Complete unit Description Descriptio	Product range		Service distribution board IVS
Doors Modular system Transparent doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock 2 mm plexiglass transparent panel Material Polyester powder coating RAL 9016, traffic white Protection type Suitable for width Suitable for height Material Material Polyester powder coating RAL 9016, traffic white 1P30 600 510	Basic function		Wall-mounting distribution system
Modular system Transparent doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock 2 mm plexiglass transparent panel Sheet steel Polyester powder coating RAL 9016, traffic white Protection type Suitable for width Suitable for height Height Modular system Transparent doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock 2 mm plexiglass transparent panel Sheet steel Polyester powder coating RAL 9016, traffic white 1930 600 510	Product function		Accessories
Transparent doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock 2 mm plexiglass transparent panel Sheet steel Polyester powder coating RAL 9016, traffic white Protection type IP30 Suitable for width Suitable for height Suitable for height Material Sheet steel IP30 Southable for height	Accessories		Doors
Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock 2 mm plexiglass transparent panel Sheet steel Polyester powder coating RAL 9016, traffic white Protection type Suitable for width Suitable for height Height Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock 2 mm plexiglass transparent panel Sheet steel Polyester powder coating RAL 9016, traffic white IP30 600 510 600 600 600 600 600 600 600 600 600 6	Single unit/Complete unit		Modular system
Forecasting RAL 9016, traffic white Protection type Suitable for width Suitable for height Height IP30 600 510 mm 510	Description		Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 1-point long with three-point turn-lock
RAL 9016, traffic white RAL 9016, traffic white Protection type Frotection type Suitable for width Suitable for height Height RAL 9016, traffic white RAL 9016, traffic white Protection type Protection type Frotection type	Material		Sheet steel
Suitable for width Suitable for height	Surface finish		
Suitable for height 510 Height 510	Protection type		IP30
deight mm 510	Suitable for width		600
	Suitable for height		510
Vidth mm 600	Height	mm	510
••••	Width	mm	600