



Wall enclosure, +mounting plate, HxWxD=800x600x200mm

Part no. CS-86/200
Article no. 111706

Delivery program

Product range			Wall-mounting housing CS
Product function			Wall-mounting housing with mounting plate
Degree of Protection			IP66 IP23 (with ventilating plates)
Description			Foamed polyurethane sealing throughout. Impact resistance category IK09 to EN 62262. Sheet steel mounting plate Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120° Door hinge pins with quick change technology. Standardized locking system with sash fastener. Powder coating RAL 7035 inside and outside
Material			Steel plate
Dimensions			
Width		mm	600
Height		mm	800
Depth		mm	200
Locks	Number		2
Hinges	Number		3
Door profile molding	Number		2
Flange plates	Width x Depth	mm	172 x 532
Max. F3A flanges	Number		2
Mounting plates			
Height		mm	770
Width		mm	550
Weight		kg	30.2
Information about equipment supplied			Lock, 3 mm double ward key Including M6 threaded welded studs for earth conductor connections in the door

Technical data

General

Standards			IEC/EN 60529, IEC 62262, IEC/EN 62208
RoHS			In accordance with Directive 2002/95/EC of the European Parliament and Council
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			yes
Climatic proofing			Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30
Ambient temperature		°C	-40 - +70
Degree of Protection			IP66 IP23 (with ventilating plates)
Installation conditions			Indoor-/outdoor installation
Power loss			
			Power loss P_v [W] for fully enclosed sheet steel enclosure CS without internal partitions for wall mounting. Example: max. ambient temperature 35°C; Overtemperature $\Delta T = 20$ K; Relative humidity = 75%.
Max. heat dissipation			
Individual enclosure for wall mounting	P_v	W	68
Starting enclosure for wall mounting	P_v	W	64
Middle enclosure for wall mounting	P_v	W	60

Material characteristics

Material			Steel plate
Surface treatment			Structured powder spray polyester based paint finish
Surface finish			Semi-textured
Colour			light gray (RAL 7035)

Finish		Gloss
Material thickness	mm	
Body	mm	1.5
Mounting plate	mm	3
Door	mm	1.5
Bottom plate	mm	1.5

Material properties

Mechanical			
Impact resistance			IK09 according to EN 62262
max. assembly weights			
Total of Weight of fitted components	kg		325
Mounting plate	kg		300
Door	kg		25
			500 kg payload, when brackets fitted in all four enclosure corners (vertically or horizontally) and the weights are symmetrically distributed within the enclosure.

Description/standard features

Construction			Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure.
Back plate			9 mm drilling dimensions for wall mounting
Side plates			Without apertures
Top plate			Without apertures
Bottom plate			Enclosed, foamed gasket, can be unscrewed for F3A-... flanges or for assembly by user
Mounting plate, material			Sheet steel, hot-galvanized
Door, Engineering			Including M6 threaded welded studs for earth conductor connections in the door:
Information about equipment supplied			Lock, 3 mm double ward key Including M6 threaded welded studs for earth conductor connections in the door
			If electrical apparatus is to be installed in the door, a continuous, permanent protective ground contactor connection must be established with a protective ground cable. The threaded welded studs on the door and on the cabinet side wall must be used as connecting points for the ground leads.
Door hinges			On the right, can be converted by user
Type Door			Door hinges right can be converted by user
door opening angle			120°
Door interlock			Protection insulated turn-buckle Standard closure 3 mm double-ward key
Locks	Number		2

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees, calculated as per IEC 60890			
Individual enclosure for wall mounting	P _V	CO	65
Starting enclosure for wall mounting	P _V	CO	62
Middle enclosure for wall mounting	P _V	CO	59
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees, calculated as per IEC 60890			
Individual enclosure for wall mounting	P _V	CO	131
Starting enclosure for wall mounting	P _V	CO	124
Middle enclosure for wall mounting	P _V	CO	117
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply to enclosures without lifting aids.

10.2.6 Mechanical impact			IK09
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP66_x
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			$U_i = 1000 \text{ V AC}$
10.9.3 Impulse withstand voltage			Does not apply to basic enclosures as defined in EN 62208.
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			Meets the product standard's requirements.

Approvals

Product Standards			UL 508A; CSA-C22.2 No.14; IEC/EN 60529; CE marking
UL File No.			E336299
UL Category Control No.			NITW
CSA File No.			—
CSA Class No.			—
North America Certification			Request filed for CSA
Conditions of Acceptability			Series CS may be provided with metal sub-panel. No back mounted components are allowed between sub-panel and the back sheet metal enclosure
Specially designed for North America			No
Suitable for			Industrial Control Panels
Degree of Protection			IEC: IP66, indoor and outdoor; UL/CSA Types 1, 12, indoor only.

Dimensions

Dimensions

Additional product information (links)

AWA4300-2521 CS wall-mounted sheet steel enclosures with mounting plate		
AWA4300-2521 CS wall-mounted sheet steel enclosures with mounting plate	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/25210414.pdf	
Declaration of conformity	http://intranet.moeller.net/technik_daten/file/produkt_deklarationen/file/konformitaeten/00002/00002259.pdf	