



Touch panel, 24 V DC, 7z, TFTcolor, ethernet, RS485, profibus, SWDT, PLC

Part no. **XV-102-E8-70TWRC-10**
Article no. **153528**
Catalog No. **XV-102-E8-70TWRC-10**



Powering Business Worldwide™



Delivery program

Product range		XV100 7"
Product range		XV-102
Subrange		SmartWire-DT touch display with integrated controller (HMI PLC)
Function		SmartWire-DT coordinator
Description		XV100 touch panel with PLC function for flush mounting plates
Description		Coordinator for the SmartWire-DT communications system
Common features of the model series		Ethernet interface USB device USB Host Slot for SD card UL508, cUL approvals
Display - Type		Color display, TFT
Touch-technology		Resistive-Touch
Number of colours		64 k Colours
Resolution	Pixel	WVGA 800 x 480
Portrait format		yes
Screen diagonal	Inch	7
Model		Insulating enclosure and front plate
Operating system		Windows CE 5.0 (licence incl.)
PLC-licence		PLC licence inclusive
License certificates for onboard interfaces		Not required
built-in interfaces		1 x Ethernet 10/100 Mbps 1 x RS485 1 x USB host 2.0 1 x USB device 1 x PROFIBUS/MPI 1 x SmartWire-DT
Front type		Standard front with standard membrane (fully enclosed)
Utilization		Flush mounting
Slots		for SD card: 1
Memory card automation		Optionally with SD card -> article no. 139807
Pluggable communication cards (optional)		no
Touch sensor		Glass with film
Heat dissipation	W	9.5
Connection to SmartWire-DT		yes

Technical data

Display		
Display - Type		Color display, TFT
Screen diagonal	Inch	7
Resolution	Pixel	WVGA 800 x 480
Visible screen area	mm	152 x 91
Number of colours		64 k Colours
Contrast ratio (Normally)		Normally 300:1
Brightness	cd/m ²	Normally 250
Back-lighting		LED dimmable via software
Service life of back-lighting	h	Normally 40000
Resistive touch protective screen		Touch sensor (glass with foil)
Operation		
Technology		Resistive-Touch 4 wire
Touch sensor		Glass with film

System

Processor		RISC CPU, 32 Bit, 400 MHz
Internal memory		DRAM (OS, Program and data memory): 64 MByte NAND-Flash (can be used for data backup): approx. 128 MByte available NVRAM (retained data): approx. 32 KByte available
External memory		SD Memory Card Slot: SDA Specification 1.00
Cooling		Fanless CPU and system cooling, natural convection-based passive cooling
Back-up of real-time clock		
Battery (service life)		Zero maintenance
Backup (time at zero voltage)		Normally 10 years
Operating system		Windows CE 5.0 (licence incl.)

Engineering

Visualisation software		GALILEO EPAM XSOFT-CODESYS-2 XSOFT-CODESYS-3
PLC-Programming software		XSOFT-CODESYS-2 XSOFT-CODESYS-3
Target and web visualization		Yes

Interfaces, communication

built-in interfaces		1 x Ethernet 10/100 Mbps 1 x RS485 1 x USB host 2.0 1 x USB device 1 x PROFIBUS/MPI 1 x SmartWire-DT
PLC-licence		PLC licence inclusive
USB Host		USB 2.0 (1.5 - 12 Mbit/s), not galvanically isolated
USB device		USB 2.0, not galvanically isolated
RS-232		no
RS-485		Yes
CAN		no
Profibus		Yes
Slots		for SD card: 1
SmartWire-DT master		Yes
Ethernet		100Base-TX/10Base-T
easyNet		no
MPI		Yes

Power supply

Nominal voltage		24 V DC SELV (safety extra low voltage)
permissible voltage		Effective: 19.2-30.0 V DC (rated operating voltage -20%/+25%) Absolute with ripple: 18.0-31.2 V DC Battery powered: 18.0-31.2 V DC (rated operating voltage -25%/+30%) 35 V DC for a duration of < 100 ms
Voltage dips	ms	≤ 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (19.2 V DC)
Power consumption	P _{max.}	W
Note on power consumption		10
Heat dissipation		Basic device USB Slave to USB Host: 2.5 Total: 9.5
Note on heat dissipation		Heat dissipation with power consumption for 24 V 7 W for basic device + 2.5 W for USB module
Siemens MPI, (optional)		yes
Type of fuse		Yes (fuse not accessible)
Potential isolation		no potential isolation

General

Housing material		Plastic, gray
Front type		Standard front with standard membrane (fully enclosed)
Dimensions (W x H x D)	mm	210 x 135 x 38
flush mounted		Clearance: W x H x D ≥ 30 mm (1.18") Inclination from vertical: ±45° (if using natural convection)
Weight	kg	0.6
Degree of protection (IEC/EN 60529, EN50178, VBG 4)		IP65 (at front), IP20 (at rear)

Approvals		cUL (UL508)
Explosion protection (according to ATEX 94/9/EC)		II 3D Ex II T70°C IP5x: Zone 22, Category 3D
Applied standards and directives		
EMC		(in relation to CE) EN 61000-6-2 EN 61000-6-4 EN 61131-2
Explosion protection (relevant for CE)		EN 60079-0 EN 61241-1 EN 13463_x
Product standards		EN 50178 EN 61131-2
Security		EN 60950 UL 60950
Mechanical shock resistance	g	according to IEC 60068-2-27
Vibration		according to IEC/EN 60068-2-6
RoHS		conform

Environmental conditions

Temperature			
Operation	θ	°C	0 - +50
Storage / Transport	θ	°C	-20 - +60
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	+ 50
Relative humidity			
Relative humidity			10 - 95%, non-condensing

Supply voltage U_{Aux}

Rated operational voltage	U_{Aux}	V	24 V DC (-20/+25%)
Residual ripple on the input voltage		%	≤ 5
Protection against polarity reversal			Yes
Max. current	I_{max}	A	3
Note			If contactors with a total power consumption > 3 A are connected, a power feeder module EU5C-SWD-PF1/2 has to be used.
Short-circuit rating			no, external fuse FAZ Z3
Potential isolation			No
Rated operating voltage of 24-V-DC slaves		V	typ. U_{Aux} - 0.2

Supply voltage U_{Pow}

Supply voltage	U_{Pow}	V	24 DC -20 % + 25 %
Input voltage ripple		%	≤ 5
Siemens MPI, (optional)			yes
Rated current	I	A	0.7
Overload proof			yes
Inrush current and duration		A	12.5 A/6 ms
Heat dissipation at 24 V DC		W	1.0
Potential isolation between U_{Pow} and 15 V SmartWire-DT supply voltage			No
Bridging voltage dips		ms	10
Repetition rate		s	1
Status indication		LED	yes

SmartWire-DT supply voltage

Rated operating voltage	U_e	V	14,5 ± 3 %
max. current	I_{max}	A	0.7
Note			If SmartWire-DT modules with a total power consumption > 0.7 A are connected, a power feeder module EU5C-SWD-PF2 has to be used.
Short-circuit rating			Yes

Connection supply voltages

Connection type			Push in terminals
Solid		mm ²	0.2 - 1.5
Flexible with ferrule		mm ²	0.25 - 1.5

SmartWire-DT network

Station type		SmartWire-DT master
Number of SmartWire-DT slaves		99
Baud Rates	kBd	125 250
Address allocation		automatic
Status indication	LED	SmartWire-DT master LED: red/green Configurations LED: red/green
Connections		Plug, 8-pole
Plug connectors		Blade terminal SWD4-8MF2

Design verification as per IEC/EN 61439

Technical data for design verification	I _n	A	0
Rated operational current for specified heat dissipation			
Heat dissipation per pole, current-dependent	P _{vid}	W	0
Equipment heat dissipation, current-dependent	P _{vid}	W	0
Static heat dissipation, non-current-dependent	P _{vs}	W	9.5
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	50
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Meets the product standard's requirements.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 6.0

PLC's (EG000024) / Graphic panel (EC001412)

Electric engineering, automation, process control engineering / Control / Operate and Observe (HMI) / Graphic panel (HMI) (ecl@ss8.1-27-24-23-02 [BAA722010])

Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20.4 - 28.8
Voltage type of supply voltage		DC
Number of HW-interfaces industrial Ethernet		1

Number of HW-interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		2
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces other		1
With SW interfaces		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for MODBUS		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		Yes
Radio standard Bluetooth		No
Radio standard WLAN 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
Type of display		TFT
With colour display		Yes
Number of colours of the display		65536
Number of grey-scales/blue-scales of display		0
Screen diagonal	inch	7
Number of pixels, horizontal		800
Number of pixels, vertical		480
Useful project memory/user memory	kByte	64000
With numeric keyboard		Yes
With alpha numeric keyboard		Yes
Number of function buttons, programmable		0
Number of buttons with LED		0
Number of system buttons		1
With touch screen		Yes
With message indication		Yes
With message system (incl. buffer and confirmation)		Yes
Process value representation (output) possible		Yes

Process default value (input) possible		Yes
With recipes		Yes
Number of password levels		200
Printer output available		Yes
Number of online languages		100
Additional software components, loadable		Yes
Degree of protection (IP), front side		IP65
Operation temperature	°C	0 - 50
Rail mounting possible		No
Wall mounting/direct mounting		No
Suitable for safety functions		No
Width of the front	mm	210
Height of the front	mm	135
Built-in depth	mm	33

Approvals

Product Standards	UL508, cULus; IEC/EN 61131-2, CE
UL File No.	E205091
UL Category Control No.	NRAQ
CSA File No.	UL report applies to US and Canada
CSA Class No.	-
North America Certification	UL listed, certified by UL for use in Canada
Current Limiting Circuit-Breaker	No
Degree of Protection	IEC:IP20, UL/CSA Tape: open type

Dimensions



Additional product information (links)

Instruction leaflet IL048007ZU XV-102	
Instruction leaflet IL048007ZU XV-102	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL048007ZU.pdf
MN04802004Z Operator manual XV-102	
MN04802004Z Betriebsanleitung XV-102 - Deutsch	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802004Z_DE.pdf
MN04802004Z Operator manual XV-102 - English	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802004Z_EN.pdf
MN04802013Z quick-start instructions XV100	

MN04802013Z Schnellstartanleitung XV100 - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802013Z_DE.pdf

MN04802013Z quick-start instructions XV100 - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802013Z_EN.pdf

MN04802091Z User manual XSoft-CoDeSys-2, PLC programming XV100

MN04802091Z Benutzerhandbuch XSoft-CoDeSys-2, SPS-Programmierung XV100 - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802091Z-DE.pdf

MN04802091Z User manual XSoft-CoDeSys-2, PLC programming XV100 - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802091Z-EN.pdf

MN048008ZU Manual XSOFT-CODESYS-3, PLC programming

MN048008ZU Handbuch XSOFT-CODESYS-3, SPS-Programmierung - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN048008ZU_DE.pdf

MN048008ZU Manual XSOFT-CODESYS-3, PLC programming - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN048008ZU_EN.pdf