


Transformator 230V, 4/8/12V, 2/2/1, 5A, 2HP
Part no.
Article no.
TR-G3/18
272483

Similar to illustration

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation	I _n	A	0
Heat dissipation per pole, current-dependent	P _{vid}	W	0
Equipment heat dissipation, current-dependent	P _{vid}	W	7.02
Static heat dissipation, non-current-dependent	P _{vs}	W	0
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40
			0

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Bell transformer (EC001547)

Electric engineering, automation, process control engineering / Transformer, converter, coil / Bell transformer / Bell transformer (unspecified) (ecl@ss8.1-27-03-11-90 [BAC147008])

Primary voltage	V	230
Secondary voltage 1	V	4
Secondary voltage 2	V	8
Secondary voltage 3	V	12
Secondary amperage 1	A	2
Secondary amperage 2	A	2
Secondary amperage 3	A	1.5
Max. output power	W	0
Max. output current	A	0
Max. power loss	W	0
Type of transformer		Standard bell ringing transformer
Suitable for surface mounting		Yes
Suitable for flush-mounting		No
Modular version		Yes
Length	mm	55
Width	mm	36
Height	mm	90
Width in number of modular spacings		2
Short-circuit protected		Yes
Temperature protection		Yes
On/Off switch		No