



**Auxiliary contact, 1N/O+1N/C, 4A, 250V AC**

**Part no. Z-AHK**  
**Article no. 248433**

## Delivery program

Basic function			Accessories for combined residual-current/power circuit-breakers Accessories for residual current circuit breakers Accessories for miniature circuit breaker
Basic function accessories			Auxiliary contacts
Application			Switchgear for industrial and advanced commercial applications
Product range			Accessory
Side mounting			for fitting on left to: LS, FI/LS
Contact sequence			

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-5	
Operating ambient temperature max.	°C	40	

## Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Universal
Additional equipment			Auxiliary switch
Attached at delivery			No
Assembly width (TE)			0.5
Number of normally open contacts			1
Number of normally closed contacts			1
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current	A	3	
Nominal rated voltage	V	230	
Control voltage type		AC	
With autotest for earth leakage function		No	
Suitable for max. number of poles main contact unit (total)		2	
Suitable for max. current main contact unit	A	4	

## Dimensions

