



## Pressure compensating grommet, M25, IP50\_x

Part no. **KT-M25F**  
Article no. **224556**

### Delivery program

|                      |  |    |                                                                          |
|----------------------|--|----|--------------------------------------------------------------------------|
| Accessories          |  |    | Pressure compensating plug, pressure compensating grommets               |
| Description          |  |    | Ventilation grommet with filter<br>Fitting below or on side of enclosure |
| Material             |  |    | PE and PVC                                                               |
| For use with         |  |    | Metric                                                                   |
| For use with         |  |    | CS-...                                                                   |
| Cable entry          |  |    | M25                                                                      |
| Hole diameter        |  | mm | 25,5                                                                     |
| Degree of Protection |  |    | up to IP50                                                               |

### Technical data

#### General

|                      |  |  |            |
|----------------------|--|--|------------|
| Degree of Protection |  |  | up to IP50 |
|----------------------|--|--|------------|

#### Material characteristics

|                           |  |  |                                                                                                                           |
|---------------------------|--|--|---------------------------------------------------------------------------------------------------------------------------|
| Material                  |  |  | PE and PVC                                                                                                                |
| Colour                    |  |  | Grey, RAL 7032 + white                                                                                                    |
| Temperature resistant     |  |  | 0 °C - 60 °C, short-time up to approx. 80 °C                                                                              |
| Chemical resistant        |  |  | Resistant against, diluted non-oxidising acids, lye and salt, alcohol, aromatic and halogen-free hydrocarbon, surfactant. |
| Danger of stress fracture |  |  | Relative high                                                                                                             |

### Dimensions

