


DATASHEET - MSFB-4-125A



Board, 4 outgoing, 225mm width, 125 A

Part no. MSFB-4-125A
Catalog No. 191091
Eaton Catalog No. MSFB-4-125A



Technical data

General

Standards			EN 61439-1
Interval between busbar centres		mm	60
Mounting position			horizontal
Degree of Protection			IP20
Weight		kg	0.79

Contacts

Rated operational voltage	U_e	V	690
Rated frequency	f	Hz	50/60
Rated impulse withstand voltage	U_{imp}	kV	6

Electrical data

Rated operational current	I_e	A	125
---------------------------	-------	---	-----

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Busbar system for distribution boards (EC001900)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar system for distribution boards (ecI@ss10.0.1-27-40-06-13 [ACO389011])			
Height		mm	160
Width		mm	225
Depth		mm	45
Number of poles			3
Busbar distance		mm	60
Busbar height		mm	0
Busbar thickness		mm	0
Rated current		A	125
Short-circuit breaking capacity (I _{cw})		kA	10
Material			Copper
Surface protection			Bare

Dimensions

