

## DATASHEET - 315NHM3B-690



**Fuse-link, LV, 315 A, AC 690 V, NH3, aM, IEC, dual indicator, live gripping lugs**



**Catalog No. 315NHM3B-690**

**EL-Nummer  
(Norway) 0001664159**

Similar to illustration

### Technical data ETIM 7.0

|                                                                                                                                                                                     |  |    |                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)                                                                                                             |  |    |                                   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |                                   |
| Construction size                                                                                                                                                                   |  |    | NH3                               |
| Rated current                                                                                                                                                                       |  | A  | 315                               |
| Rated voltage                                                                                                                                                                       |  | V  | 690                               |
| Voltage type                                                                                                                                                                        |  |    | AC                                |
| Rated switching capacity                                                                                                                                                            |  | kA | 120                               |
| Utilization category                                                                                                                                                                |  |    | aM (switchgear protection)        |
| Type of fuse status indicator                                                                                                                                                       |  |    | Combination fuse status indicator |
| Insulated metal gripping lugs (IMGL)                                                                                                                                                |  |    | No                                |