



Fuse-link, LV, 12 A, AC 690 V, 14 x 51 mm, aM, IEC

**Catalog No.** C14M12

**EL-Nummer  
(Norway)** 0001600245

## Technical data ETIM 7.0

|                                                                                                                                                                                               |    |                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|----------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)                                                                                                                           |    |                            |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) |    |                            |
| Size                                                                                                                                                                                          |    | 14x51 mm                   |
| Rated voltage                                                                                                                                                                                 | V  | 690 - 690                  |
| Rated voltage                                                                                                                                                                                 |    | Other                      |
| Voltage type                                                                                                                                                                                  |    | AC                         |
| Utilization category                                                                                                                                                                          |    | aM (switchgear protection) |
| Rated operating frequency                                                                                                                                                                     | Hz | 45 - 62                    |
| Nominal current                                                                                                                                                                               | A  | 12                         |
| With striker                                                                                                                                                                                  |    | No                         |
| Release characteristic                                                                                                                                                                        |    | Other                      |
| Breaking capacity                                                                                                                                                                             | kA | 80                         |