



Distribution board-light intensity switch, 2 TLE, 2-2000 Lux, w. surface mounting light sensor

Part no. SRSD1COW
Catalog No. 167378
Eaton Catalog No. SRSD1COW
EL-Nummer 0001456980
(Norway)

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	1.7
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-30
Operating ambient temperature max.		°C	55
			0

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Twilight switch for distribution board (EC001645)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Twilight switch for distribution board (ecl@ss10.0.1-27-14-23-22 [ACN363011])			
Rated voltage		V	230
Rated frequency		Hz	50 - 60
Max. incandescent lamp load		W	2300
Max. load fluorescent lamp		VA	2300
Max. load fluorescent lamp (Duo circuit)		VA	2300
Max. load fluorescent lamp (parallel compensated)		VA	400
Max. switching current (cos phi = 0.6)		A	0
Rated switch current		A	16
Adjustment range brightness value		lx	2 - 2000
With programmable overnight shutoff			No
Push button input			No
Rated voltage light sensor		V	0
Max. conductor length light sensor		m	100
Protection class light sensor			II
Mounting method light sensor			Wall surface mounted
Mounting method			DIN rail
Width in number of modular spacings			2
Built-in depth		mm	69.2
Degree of protection (IP)			IP20
Degree of protection (IP) light sensor			IP55