



## Miniature circuit breaker (MCB), 15A, 1p, type C characteristic

**Part no.** FAZ-C15/1  
**Catalog No.** 278560  
**Eaton Catalog No.** FAZ-C15/1  
**EL-Nummer** 0001691086  
**(Norway)**

Similar to illustration

## Technical data

### Electrical

|   |          |      |                                |
|---|----------|------|--------------------------------|
| Standards   |          |      | IEC/EN 60947-2<br>IEC/EN 60898 |
| Rated operational voltage   | $U_e$    | V    |                                |
|   | $U_e$    | V AC | 240/415                        |
| Rated voltage according to UL   | $U_n$    | V AC | 277                            |
| Rated switching capacity acc. to IEC/EN 60947-2   | $I_{cu}$ | kA   | 15                             |
| Breaking capacity according to UL   |          | kA   | 10 (UL1077)                    |
| Max operational voltage according to IEC/EN 60947-2   |          | V AC | 254                            |
| Rated switching capacity according to IEC/EN 60947-2 (max operational voltage)                      | $I_{cu}$ | kA   | 10                             |
| Rated service short-circuit breaking capacity according to IEC/EN 60947-2 (max operational voltage) | $I_{cs}$ |      | 7,5 kA                         |
| Rated voltage according to IEC/EN 60898-1   | $U_n$    | V AC | 240                            |
| Rated switching capacity according to IEC/EN 60898-1  | $I_{cn}$ | kA   | 10                             |
| Rated service short-circuit breaking capacity according to IEC/EN 60898-1                           | $I_{cs}$ |      | 7,5 kA                         |

## Design verification as per IEC/EN 61439

|  |            |    |   |
|--|------------|----|---|
| Technical data for design verification   |            |    |   |
| Rated operational current for specified heat dissipation   | $I_n$      | A  | 15  |
| Heat dissipation per pole, current-dependent   | $P_{vid}$  | W  | 0   |
| Equipment heat dissipation, current-dependent  | $P_{vid}$  | W  | 2.1   |
| Static heat dissipation, non-current-dependent   | $P_{vs}$   | W  | 0   |
| Heat dissipation capacity  | $P_{diss}$ | W  | 0   |
| Operating ambient temperature min.   |            | °C | -40   |
| Operating ambient temperature max.   |            | °C | 75  |
|  |            |    | linear, per +1 °C, results in a 0.5% reduction of current carrying capacity |
| IEC/EN 61439 design verification   |            |    |   |
| 10.2 Strength of materials and parts   |            |    |   |
| 10.2.2 Corrosion resistance  |            |    |   |
| 10.2.3.1 Verification of thermal stability of enclosures   |            |    |   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |            |    |   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |    |   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |            |    |   |
| 10.2.5 Lifting   |            |    |   |
| 10.2.6 Mechanical impact   |            |    |   |
| 10.2.7 Inscriptions  |            |    |   |
| 10.3 Degree of protection of ASSEMBLIES  |            |    |   |
| 10.4 Clearances and creepage distances   |            |    |   |
| 10.5 Protection against electric shock   |            |    |   |
| 10.6 Incorporation of switching devices and components   |            |    |   |
| 10.7 Internal electrical circuits and connections  |            |    |   |
| 10.8 Connections for external conductors   |            |    |   |

|  |  |  |  |
|--|--|--|--|
| 10.9 Insulation properties                               |  |  |  |
| 10.9.2 Power-frequency electric strength                 |  |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage                         |  |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material |  |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                               |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                      |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0

|   |  |                 |          |
|---|--|-----------------|----------|
| Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)  |  |                 |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecI@ss10.0.1-27-14-19-01 [AAB905014]) |  |                 |          |
| Release characteristic  |  |                 | C        |
| Number of poles (total)   |  |                 | 1        |
| Number of protected poles   |  |                 | 1        |
| Rated current   |  | A               | 15       |
| Rated voltage   |  | V               | 230      |
| Rated insulation voltage Ui   |  | V               | 440      |
| Rated impulse withstand voltage Uimp  |  | kV              | 4        |
| Rated short-circuit breaking capacity Icn EN 60898 at 230 V   |  | kA              | 10       |
| Rated short-circuit breaking capacity Icn EN 60898 at 400 V   |  | kA              | 10       |
| Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V  |  | kA              | 15       |
| Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V  |  | kA              | 15       |
| Voltage type  |  |                 | AC       |
| Frequency   |  | Hz              | 50 - 60  |
| Current limiting class  |  |                 | 3        |
| Suitable for flush-mounted installation   |  |                 | No       |
| Concurrently switching N-neutral  |  |                 | No       |
| Over voltage category   |  |                 | 3        |
| Pollution degree  |  |                 | 2        |
| Additional equipment possible   |  |                 | Yes      |
| Width in number of modular spacings   |  |                 | 1        |
| Built-in depth  |  | mm              | 70.5     |
| Degree of protection (IP)   |  |                 | IP20     |
| Ambient temperature during operating  |  | °C              | -25 - 75 |
| Connectable conductor cross section multi-wired   |  | mm <sup>2</sup> | 1 - 25   |
| Connectable conductor cross section solid-core  |  | mm <sup>2</sup> | 1 - 25   |

## Approvals

|                                  |  |  |  |
|----------------------------------|--|--|--|
| Product Standards                |  |  | IEC/EN 60947-2; IEC/EN 60898; UL 1077; CSA-C22.2 No. 235; CE marking |
| UL File No.                      |  |  | E177451  |
| UL Category Control No.          |  |  | QVNU2, QVNU8   |
| CSA File No.                     |  |  | 204453   |
| CSA Class No.                    |  |  | 3215-30  |
| North America Certification      |  |  | UL recognized, CSA certified   |
| Conditions of Acceptability      |  |  | Supplementary Protector only   |
| Suitable for                     |  |  | Branch Circuits; not as BCPD   |
| Current Limiting Circuit-Breaker |  |  | No   |
| Max. Voltage Rating              |  |  | 277 VAC; 48 VDC  |
| Degree of Protection             |  |  | IEC: IP20; UL/CSA Type: -  |