

## Protective cover IP55, fixed mounted design

**Part no.** IZMX-DC40-F-1  
**Article no.** 184236  
**Catalog No.** 68D2539G04

### Delivery program

|                                      |  |  |   |
|--------------------------------------|--|--|---|
| Product range                        |  |  | Accessories   |
| Accessories                          |  |  | Degree of protection IP55   |
| Accessories                          |  |  | Protective cover  |
|                                      |  |  | The front of the circuit-breaker projects through the door cut-out.<br>The protective cover covers the circuit-breaker and the door cut-out and makes it possible to have an IP55 degree of protection.<br>The protective cover can be swung open to the left or right. |
| For use with                         |  |  | IZMX40...F<br>INX40...F   |
| Information about equipment supplied |  |  | The mounting kit includes a protective cover, a hinge, a door seal, and fixing material.  |
| Installation type                    |  |  | Fixed   |

### Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

### Technical data ETIM 6.0

|   |  |  |       |
|---|--|--|-------|
| Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)   |  |  |       |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Component for low-voltage switch technology (accessories) (ecl@ss8.1-27-37-92-01 [AKN570010]) |  |  |       |
| Type of accessory   |  |  | Cover |

Dimensions



