




Insulated enclosure, HxWxD=500x250x225mm, for size 2

Part no. NZM2-XCI45-TVDVR
Article no. 279356

Similar to illustration

Delivery program

				
Product range				Accessories
Accessories				Insulated enclosures
Description				With door coupling rotary handle Complete with all required functional parts
Function				Red-yellow for emergency switching off
Locking facility				Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock.
Accessories				Accessories, others
Number of poles				3/4 pole
Standard/Approval				IEC
Construction size				NZM2
Degree of Protection				IP64
Rated uninterrupted current I_u at max. cross-section	I_u	A		250 A
Basic enclosure				CI45-200
Terminal for retrofitting of 5th conductor (neutral conductor)				K10/1, K25/1, K50/1, K95/1N/BR, K150/1/BR, K240/1/BR
For use with				NZM2(-4), PN2(-4), N(S)2(-4)
Notes				
Suitable for installation of circuit-breakers and switch-disconnectors Enclosure for separate mounting with top and bottom cable entry.				
Include fixing straps for wall mounting.				
Cannot be used in combination with NZM...-XR... remote operator..., NZM...-XSV plug-in unit or NZM...-XAV withdrawable unit.				
Insulated additional terminal for 4th or 5th pole should be ordered separately.				
CI-K5 enclosure with hard metric knock-outs				
CI23 enclosure with flanges				
CI43, CI45 and CI48 feature gland plates.				
Only for switches with box terminal for direct connection of cables.				

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ecl@ss8.1-27-37-13-01 [AKN343011])			
Material housing			Plastic
Width		mm	375
Height		mm	500
Depth		mm	225
With transparent cover			Yes
Suitable for emergency stop			Yes
Model			Surface mounting
Degree of protection (IP)			IP65

Dimensions

