



Digital residual current circuit-breaker/miniature circuit-breaker, 15A, 30mA, miniature circuit-breaker trip curve: B, 2 p, residual current circuit-breaker trip characteristic: G/A

Part no. dRBM-15/2/B/003-G/A-OL
Catalog No. 168233

Similar to illustration

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	15
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	4.5
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss8.1-27-14-22-07 [AFZ810012])			
Number of poles (total)			2
Number of protected poles			2
Nominal rated voltage		V	240
Nominal rated current		A	15
Rated fault current		A	0.03
Leakage current type			A
Current limiting class			3
Rated short-circuit breaking capacity EN 60898		kA	10
Rated short-circuit breaking capacity IEC 60947-2		kA	0
Frequency			50 Hz
Release characteristic			B
Concurrently switching N-neutral			No
Over voltage category			3
Pollution degree			2
Width in number of modular spacings			2
Built-in depth		mm	75
Suitable for flush-mounted installation			No
Degree of protection (IP)			IP20
Surge current capacity		kA	3
Voltage type			AC
Antinuisance tripping version			Yes