



# Style Variant 28011 LED CGLine

Escape sign luminaire



28011 LED with cover PR



## Style Variant 28011 LED CGLine

- Self-monitoring LED self-contained luminaire for stand-alone operation or for connection to the self-contained luminaire monitoring system CGLine+ (see page 5.7)
- Selectable operating time: 1 h or 3 h
- Minimum service requirement due to high service life of the LEDs (50,000 hours)
- Brightness selectable in 3 steps
- Test results with fault analysis (LED, charging and battery circuit) as well as status display (operation, function test, duration test) via 3 coloured LEDs
- Automatic function test (weekly) and duration test (every 3 months)
- Manual function test or operational duration test via testing buttons
- Automatic charging monitoring and deep discharge protection with restart inhibit
- 1 minute delay of normal mode after mains returns (acc. to DIN VDE 0100-718)
- Blocking function with CGLine+ Web-Controller in times of shut-down
- Luminaires are generally suitable for maintained or non-maintained mode


Viewing distance	32 m
Luminous flux $\Phi_E/\Phi_N$ at end of rated operating time	50 % 1 h 20 % 3 h
Housing material	Polycarbonate (850 °C glow wire resistant)
Housing colour	Light grey, sim. RAL 7035
Weight	1.2 kg
Type of mounting	Wall mounting
Connection terminals	Mains connection 3 x 2.5 mm <sup>2</sup> / Bus connection 2 x 1.5 mm <sup>2</sup>
Connection voltage	230 V AC, 50 Hz
Power consumption mains operation	6.4 VA
Permissible ambient temperature	Maintained mode -5 °C to +30 °C Non-maintained mode 0 °C to +35 °C
Battery	Maintenance free and gas tight NiMh 4.8 V / 1.1 Ah
Light source	3 x HighPower LEDs

## Ordering details

Type	Scope of delivery	Order No.
Escape sign luminaire 28011 1-3/D LED CGLine	single-sided, without cover	40071352221
Cover PL acc. to ISO 7010	Cover with silkscreened pictogram	40071354130
Cover PR acc. to ISO 7010	Cover with silkscreened pictogram	40071354131
Cover PU acc. to ISO 7010	Cover with silkscreened pictogram	40071354132

## Accessories

Type	Order No.
Wire guard	40071348370
Through-wiring set PE, N, L, L and D1, D2	40071350422



Through-wiring set



**Switch to CGLine+ technology in Q3/2015.**  
Please visit [www.ceag.de/en](http://www.ceag.de/en) for additional information.