







13812 CGLine+ with asymmetric optics



13822 CGLine+ with symmetric optics



GuideLed SL 13812, 13822 CGLine+

- LED self contained luminaire with automatic test for reduced inspection effort
- Universal use for maintained and non-maintained operation and for 1 h, 3 h or 8 h operation
- For autonomous installation or connection to the CGLine+ monitoring system
- Environmentally-friendly due to modern lithium ion technology
- Low operating costs via low connected load
- Minimum maintenance effort via high LED service life (up to 50,000 hours)
- Available with special optics for escape route illumination or open-area illumination
- High spacing via double optics technology and highly efficient High Power LEDs
- Simple fault analysis and status display via bicolor LED and testing button
- 1 minute switch-back delay after mains return
- Blocking function prevents unintended discharge during idle operating times (only with CGLine+ WEB-Controller)

Luminous flux (mains operation)	asymmetric optics symmetric optics	210 lm 204 lm
Luminous flux Φ_E/Φ_N at end of rated operating time		100 % at 1 h; 65 % at 3 h; 25 % at 8 h
Housing material		Polycarbonate, aluminium
Housing colour		White, similar to RAL 9010
Weight		0.86 kg
Type of mounting		Ceiling surface-mounting
Terminals		Through-wiring from mains (L, L', N, PE) to 2.5 mm ² CGLine+ bus through-wiring to 1.5 mm ²
Connection voltage		220 - 240 V AC, 50/60 Hz
Power consumption mains operation (apparent power / effective power)		6.9 VA / 6.7 W
Permissible ambient temperature		Maintained mode -5 °C to +30 °C Non-maintained mode 0 °C to +35 °C
Battery		Lithium ion 3.7 V/4000 mAh with multiple protective circuit
Light source		HighPower LEDs 2 x 1.6 W

Ordering details


Scope of delivery	Order No.
GuideLed SL ceiling surface-mounted 13812 1-8h/D CGLine+ with asymmetric optics for escape route illumination, white RAL 9010	40071353279
GuideLed SL ceiling surface-mounted 13822 1-8h/D CGLine+ with symmetric optics for anti-panic/open-area illumination, white RAL 9010	40071353278



5

Measurement level 0.02 m, maintenance factor MF = 80 %, battery operation, distances in m


Emergency light oper- ating duration	Mounting height in metres	Mounting types	Mounting distance (m)			
			L1 	L2 	L3 	L4 
1 h	2.5	Ceiling mounting	1.6 (2.9)	5.8 (7.4)	5.9 (6.6)	13.2 (14.7)
	3.0	Escape route centre	1.3 (3.0)	5.8 (7.9)	6.6 (7.5)	15.0 (16.6)
	3.5		1.1 (2.2)	4.5 (8.2)	7.3 (8.3)	16.6 (18.5)
	4.0		1.1 (1.9)	3.9 (8.4)	8.1 (9.0)	18.0 (20.3)
	4.5		1.1 (1.7)	3.4 (7.3)	8.7 (9.7)	19.3 (22.0)
	5.0		1.1 (1.6)	3.2 (6.3)	9.4 (10.4)	20.9 (23.6)
	5.5		1.0 (1.5)	3.0 (5.7)	10.0 (11.2)	22.4 (25.0)
	6.0		1.0 (1.5)	3.0 (5.1)	10.5 (11.9)	23.8 (26.4)
	6.5		1.0 (1.5)	3.1 (4.7)	3.6 (12.6)	20.6 (27.8)
	7.0		1.0 (1.5)	3.0 (4.6)	3.5 (13.2)	19.0 (29.3)
	7.5		0.9 (1.5)	3.0 (4.3)	3.4 (13.8)	19.2 (30.8)
	8.0		0.9 (1.4)	2.9 (4.2)	3.3 (14.4)	19.6 (32.3)
8.5		0.8 (1.4)	2.9 (4.3)	3.1 (14.9)	20.0 (33.7)	
3 h	2.5	Ceiling mounting	1.0 (2.3)	4.5 (6.4)	5.4 (6.2)	12.3 (13.7)
	3.0	Escape route centre	0.9 (1.7)	3.4 (6.7)	6.2 (6.9)	13.9 (15.6)
	3.5		0.9 (1.4)	2.9 (6.5)	6.9 (7.6)	15.3 (17.3)
	4.0		0.9 (1.3)	2.6 (5.1)	7.5 (8.4)	16.7 (18.9)
	4.5		0.8 (1.2)	2.4 (4.5)	8.1 (9.1)	18.2 (20.4)
	5.0		0.8 (1.2)	2.5 (4.0)	8.7 (9.8)	19.6 (21.7)
	5.5		0.8 (1.2)	2.5 (3.7)	2.8 (10.4)	15.6 (23.2)
	6.0		0.8 (1.2)	2.4 (3.5)	2.7 (11.1)	15.5 (24.7)
	6.5		0.7 (1.1)	2.3 (3.4)	2.6 (11.6)	15.8 (26.2)
	7.0		0.5 (1.1)	2.3 (3.5)	2.4 (12.2)	16.3 (27.5)
	7.5		0.2 (1.1)	2.3 (3.5)	0.7 (4.0)	8.1 (23.0)
8 h	2.5	Ceiling mounting	0.5 (0.8)	1.6 (3.2)	4.7 (5.2)	10.4 (11.8)
	3.0	Escape route centre	0.5 (0.8)	1.5 (2.6)	5.3 (5.9)	11.9 (13.2)
	3.5		0.5 (0.8)	1.5 (2.3)	1.7 (6.6)	9.5 (14.6)
	4.0		0.4 (0.7)	1.4 (2.1)	1.6 (7.2)	9.8 (16.1)
	4.5		0.2 (0.7)	1.4 (2.2)	1.3 (2.5)	5.1 (15.7)



Escape route illumination
with symmetric optics

Planning help for GuideLed SL CGLine+ with symmetric optics for E = 1.0 lx (0.5 lx)
Measurement level 0.02 m, maintenance factor MF = 80 %, battery operation, distances in m

Emergency light opera- ting duration	Mounting height in metres	Mounting types	L1 	L2 	L3 	L4 
1 h	2.5	Ceiling mounting	3.8 (4.5)	9.0 (10.2)	4.2 (4.9)	9.7 (11.4)
	3.0	Escape route centre	4.1 (5.0)	10.0 (11.5)	4.4 (5.4)	10.9 (12.4)
	3.5		4.0 (5.4)	10.8 (12.7)	4.4 (5.9)	11.8 (13.7)
	4.0		3.4 (5.8)	11.5 (13.7)	2.4 (6.2)	12.3 (14.9)
	4.5		1.7 (5.8)	11.6 (14.6)	1.7 (6.4)	10.9 (15.9)
	5.0		1.3 (5.6)	11.0 (15.4)	1.3 (6.2)	10.3 (16.7)
	5.5		0.6 (5.1)	10.2 (16.1)	0.6 (5.4)	9.2 (17.3)
3 h	2.5	Ceiling mounting	3.3 (4.1)	8.2 (9.5)	3.6 (4.5)	8.9 (10.2)
	3.0	Escape route centre	3.1 (4.5)	9.0 (10.6)	3.4 (4.9)	9.7 (11.5)
	3.5		1.5 (4.7)	9.4 (11.5)	1.5 (5.1)	9.0 (12.6)
	4.0		1.0 (4.6)	8.9 (12.4)	1.1 (5.0)	8.3 (13.5)
	4.5		0.4 (4.0)	8.0 (13.1)	0.4 (3.0)	6.1 (14.0)
8 h	2.5	Ceiling mounting Escape route centre	0.6 (2.8)	5.5 (7.7)	0.7 (3.1)	5.2 (8.4)



Room illumination
with symmetric optics

Planning help for GuideLed SL CGLine+ with symmetric optics for E = 1.0 lx (0.5 lx)
Measurement level 0.02 m, maintenance factor MF = 80 %, battery operation, distances in m

Emergency light opera- ting duration	Mounting height in metres	Mounting types	L1 	L2 	L3 	L4 
1 h	2.5	Ceiling mounting	3.4 (4.3)	8.8 (10.2)	3.2 (3.9)	8.1 (9.0)
	3.0	Room illumination	3.4 (4.5)	9.4 (11.3)	3.5 (4.2)	9.4 (10.3)
	3.5		3.4 (4.4)	10.3 (12.5)	3.5 (4.2)	10.2 (11.3)
	4.0		3.4 (4.4)	11.0 (13.5)	3.4 (4.2)	10.9 (12.3)
	4.5		0.7 (4.9)	11.3 (13.9)	1.6 (4.7)	11.5 (13.7)
	5.0		0.6 (5.0)	10.5 (14.7)	1.1 (4.7)	11.4 (14.5)
	5.5		0.5 (4.4)	10.1 (15.5)	0.5 (4.5)	11.3 (15.1)
	6.0		0.7 (2.4)	10.8 (15.9)	0.5 (2.5)	10.0 (15.9)
	6.5		0.5 (0.7)	9.9 (15.6)	0.5 (1.9)	10.3 (16.2)
	7.0		0.5 (0.7)	9.1 (14.9)	0.5 (1.6)	9.9 (16.1)
3 h	2.5	Ceiling mounting	2.9 (3.4)	7.7 (9.5)	2.9 (3.3)	7.7 (8.3)
	3.0	Room illumination	3.0 (4.0)	8.5 (10.4)	2.9 (3.5)	8.5 (9.5)
	3.5		1.4 (4.0)	9.2 (11.0)	2.0 (3.8)	9.1 (10.8)
	4.0		0.5 (4.1)	8.5 (11.7)	1.1 (4.0)	9.2 (11.7)
	4.5		0.7 (4.0)	8.2 (12.4)	0.5 (3.4)	8.9 (12.4)
	5.0		0.7 (1.4)	8.3 (13.0)	0.5 (1.9)	8.3 (13.0)
8 h	2.5	Ceiling mounting	0.6 (2.4)	5.2 (7.2)	0.9 (2.7)	5.7 (7.3)
	3.0	Room illumination	0.7 (1.4)	5.4 (8.0)	0.5 (2.1)	5.0 (7.9)
	3.5		0.5 (0.7)	4.6 (7.5)	0.5 (0.9)	4.9 (8.0)
	4.0		0.6 (0.5)	4.0 (7.0)	0.5 (0.5)	3.9 (8.0)
	4.5		0.7 (0.6)	2.4 (7.2)	0.5 (0.5)	2.5 (7.2)
	5.0		0.5 (0.5)	1.4 (6.4)	0.5 (0.5)	1.4 (6.9)