

**Combined arrester, transient voltage surge suppression T1&T2**

**Part no.** **SPRT12-350/3-AX**  
**Catalog No.** **195235**

**EL-Nummer  
(Norway)** **1600137**

**EATON®**  
Powering Business Worldwide™

**Delivery program**

Products		Surge arresters
Application field		Residential buildings Utility buildings Open areas

**Technical data ETIM 7.0**

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)		
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Combined lightning current/surge arrester f. power supply s. (ecl@ss10.0.1-27-13-08-08 [ACN284011])		
System configuration DC		No
System configuration IT		No
System configuration TN		Yes
System configuration TN-C		Yes
System configuration TN-C-S		Yes
System configuration TN-S		No
System configuration TT		No
System configuration other		No
Number of poles		3
Lightning impulse current (10/350 µs)	kA	25
Max. continuous voltage AC	V	350
Max. continuous voltage DC	V	0
Nominal voltage AC	V	240
Nominal voltage DC	V	0
Max. PV-voltage	V	0
Voltage protection level	kV	1.5
Voltage protection level L-N	kV	1.5
Voltage protection level L-PE	kV	0
Voltage protection level N-PE	kV	0
Voltage protection level (DC+ - DC-)	kV	0
Voltage protection level (DC+/DC- - PE)	kV	0
Follow current extinguishing capability	kA	50
Specific energy (W/R)	kJ/Ohm	160
Max. conductor cross section solid (solid, stranded)	mm²	35
Max. conductor cross section flexible (fine-strand)	mm²	35
Mounting method	DIN rail (top hat rail) 35 mm	
Construction size	6 modular spacing	
Remote signalling	Yes	
Signalling at the device	Optic	
Test class	Type 1 + 2	
Exhausting	No	
Integrated backup fuse	No	
Energy-coordinated protection effect with regard to the terminal equipment		Yes
Degree of protection (IP)		IP20