

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

NZML2-4-VE100 - Circuit-breaker, 4p, 100A



265949 NZML2-4-VE100

[Overview](#) [Specifications](#) [Resources](#)



265949 NZML2-4-VE100

Circuit-breaker, 4p, 100A

Alternate Catalog No.

NZML2-4-VE100

EL-Nummer (Norway)

4300392

Circuit-breaker NZM2, 4 pole, Switching capacity 400/415 V 50 Hz(I_{cu}): 150 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current(I_n = I_u): 100 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Characteristics](#)
- [Dimensions](#)

Delivery program

Product range

Circuit-breaker

Protective function

Systems, cable, selectivity and generator protection

Standard/Approval

IEC

Installation type

Fixed

Release system

Electronic release

Construction size

NZM2

Description

R.m.s. value measurement and “thermal memory”

Adjustable time delay setting to overcome current peaks t_r at $6 \times I_r$ also infinity (without overload releases)

Adjustable delay time t_{sd}

i^2t constant function: fixed OFF

Set value in neutral conductor is synchronous with set value I_r of main pole.







Number of poles

4 pole

Standard equipment

Screw connection

Switching capacity

400/415 V 50 Hz [I_{cu}]
 150 kA
 Rated current = rated uninterrupted current [$I_n = I_u$]
 Rated current = rated uninterrupted current [$I_n = I_u$]
 100 A
 Neutral conductor [% of phase conductor]
 100 %
Setting range
 Overload trip  [I_t]
 50 - 100 A
 Overload trip Main pole  [I_t]
 50 - 100 A
 Short-circuit releases  [I_{rm}] Non-delayed  [$I_t = I_n \times \dots$]
 1200 A fixed
 Short-circuit releases  [I_{rm}] Delayed  [$I_{sd} = I_t \times \dots$]
 2 - 10

Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g


Safe isolation to EN 61140 Between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

Vertical and 90° in all directions	
	With XFI earth-fault release:
	- NZM1, N1, NZM2, N2: vertical and 90° in all directions
	with plug-in unit
	- NZM1, N1, NZM2, N2: vertical, 90° right/left
	with withdrawable unit:
	- NZM3, N3: vertical, 90° right/left
- NZM4, N4: vertical	
with remote operator:	
- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions	

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [$I_n = I_u$]

100 A

Rated surge voltage invariability [U_{imp}] Main contacts

8000 V

Rated surge voltage invariability [U_{imp}] Auxiliary contacts

6000 V
Rated operational voltage [U_b]
690 V AC
Overvoltage category/pollution degree
III/3
Rated insulation voltage [U_i]
1000 V
Use in unearthed supply systems
 690 V
Switching capacity
Rated short-circuit making capacity [I_{cm}]240 V [I_{cm}]
330 kA
Rated short-circuit making capacity [I_{cm}]400/415 V [I_{cm}]
330 kA
Rated short-circuit making capacity [I_{cm}]440 V 50/60 Hz [I_{cm}]
286 kA
Rated short-circuit making capacity [I_{cm}]525 V 50/60 Hz [I_{cm}]
220 kA
Rated short-circuit making capacity [I_{cm}]690 V 50/60 H [I_{cm}]
176 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]240 V 50/60 Hz [I_{cu}]
150 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]400/415 V 50/60 Hz [I_{cu}]
150 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]440 V 50/60 Hz [I_{cu}]
130 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]525 V 50/60 Hz [I_{cu}]
100 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cu} to IEC/EN 60947 test cycle O-t-CO [I_{cu}]690 V 50/60 Hz [I_{cu}]
80 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]240 V 50/60 Hz [I_{cs}]
150 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]400/415 V 50/60 Hz [I_{cs}]
150 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]440 V 50/60 Hz [I_{cs}]
130 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]525 V 50/60 Hz [I_{cs}]
100 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}] I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]690 V 50/60 Hz [I_{cs}]
80 kA
Rated short-circuit breaking capacity I_{cn} [I_{cn}]
Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.
Rated short-time withstand current I_{cw} = 0.3 s [I_{cw}]
1.3 kA
Rated short-time withstand current I_{cw} = 1 s [I_{cw}]
1.3 kA
Utilization category to IEC/EN 60947-2
A
Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]
20000
Lifespan, electrical AC-1400 V 50/60 Hz [Operations]
10000
Lifespan, electrical AC-1415 V 50/60 Hz [Operations]
10000
Lifespan, electrical AC-1690 V 50/60 Hz [Operations]
7500
Lifespan, electrical AC-3400 V 50/60 Hz [Operations]
6500
Lifespan, electrical AC-3415 V 50/60 Hz [Operations]
6500
Lifespan, electrical AC-3690 V 50/60 Hz [Operations]
5000
Lifespan, electrical Max. operating frequency
120 Ops/h
Total break time at short-circuit
< 10 ms
Terminal capacity
Standard equipment

Screw connection
 Optional accessories
 Box terminal
 Tunnel terminal
 connection on rear
 Round copper conductor Box terminal Solid
 1 x (10 - 16)
 2 x (6 - 16) mm²
 Round copper conductor Box terminal Stranded
 1 x (25 - 185)
 2 x (25 - 70) mm²
 Round copper conductor Tunnel terminal Solid
 1 x 16 mm²
 Round copper conductor Tunnel terminal Stranded 1-hole
 1 x (25 - 185) mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Solid
 1 x (10 - 16)
 2 x (6 - 16) mm²
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (25 - 185)
 2 x (25 - 70) mm²
 Al circular conductor Tunnel terminal Solid
 1 x 16 mm²
 Al circular conductor Tunnel terminal Stranded Stranded
 1 x (25 - 185) mm²
 Al circular conductor Bolt terminal and rear-side connection Direct on the switch Solid
 1 x (10 - 16)
 2 x (10 - 16) mm²
 Al circular conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (25 - 50)
 2 x (25 - 50) mm²
 Cu strip (number of segments x width x segment thickness) Box terminal [min.]
 2 x 9 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Box terminal [max.]
 10 x 16 x 0.8
 (2x) 8 x 15.5 x 0,8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [min.]
 2 x 16 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [max.]
 10 x 24 x 0.8 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection
 M8
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]
 16 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]
 24 x 8 mm
 Control cables
 1 x (0.75 - 2.5)
 2 x (0.75 - 1.5) mm²

Design verification as per IEC/EN 61439

Technical data for design verification
 Rated operational current for specified heat dissipation [I_n]
 100 A
 Equipment heat dissipation, current-dependent [P_{vid}]
 8.25 W
 Operating ambient temperature min.
 -25 °C
 Operating ambient temperature max.
 +70 °C
 IEC/EN 61439 design verification
 10.2 Strength of materials and parts 10.2.2 Corrosion resistance
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.5 Lifting
 Does not apply, since the entire switchgear needs to be evaluated.
 10.2 Strength of materials and parts 10.2.6 Mechanical impact
 Does not apply, since the entire switchgear needs to be evaluated.
 10.2 Strength of materials and parts 10.2.7 Inscriptions
 Meets the product standard's requirements.
 10.3 Degree of protection of ASSEMBLIES
 Does not apply, since the entire switchgear needs to be evaluated.
 10.4 Clearances and creepage distances
 Meets the product standard's requirements.
 10.5 Protection against electric shock
 Does not apply, since the entire switchgear needs to be evaluated.
 10.6 Incorporation of switching devices and components
 Does not apply, since the entire switchgear needs to be evaluated.
 10.7 Internal electrical circuits and connections
 Is the panel builder's responsibility.
 10.8 Connections for external conductors
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.2 Power-frequency electric strength
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.3 Impulse withstand voltage
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
 Is the panel builder's responsibility.
 10.10 Temperature rise
 The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
 10.11 Short-circuit rating
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.
 10.12 Electromagnetic compatibility
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.
 10.13 Mechanical function
 The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I_n

100 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz

150 kA

Overload release current setting

50 - 100 A

Adjustment range short-term delayed short-circuit release

100 - 1000 A

Adjustment range undelayed short-circuit release

1200 - 1200 A

Integrated earth fault protection

No

Type of electrical connection of main circuit

Screw connection

Device construction

Built-in device fixed built-in technique

Suitable for DIN rail (top hat rail) mounting

No

DIN rail (top hat rail) mounting optional

Yes

Number of auxiliary contacts as normally closed contact
0

Number of auxiliary contacts as normally open contact
0

Number of auxiliary contacts as change-over contact
0

With switched-off indicator
No

With under voltage release
No

Number of poles
4

Position of connection for main current circuit
Front side

Type of control element
Rocker lever

Complete device with protection unit
Yes


Motor drive integrated
No

Motor drive optional
Yes


Degree of protection (IP)
IP20

Characteristics

Characteristic curve




Characteristic curve



Let-through current

Characteristic curve



Let-through energy

Dimensions



- Blow out area, minimum clearance to adjacent parts
- Minimum clearance to adjacent parts

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

edz files


- [DA-CE-ETN.NZM2-4-VE100](#)
File

(Web)

Additional product information

- [Temperature dependency, Derating](#)
(Web)
- [additional technical information for NZM power switch](#)
(PDF)




Dimensions single product

- [123X341](#)
Line drawing
Circuit-breakers, switch-disconnectors
- 
[123X508](#)
Line drawing
Circuit-breaker, switch-disconnector, 4-pole
 - Blow out area, minimum clearance to adjacent parts
 - Minimum clearance to adjacent parts
 - Does not apply to DC applications

Product photo

- 
[1230PIC-805](#)
Photo

Characteristic curve

- 
[1230DIA-172](#)
Coordinate visualization
- 
[1230DIA-173](#)
Coordinate visualization
- 
[123U180](#)
Coordinate visualization
NZM2-VE100...250 tripping characteristic

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

