

Combination arrester, 3-pole




V 25-B+C/...: Combination arrester set, lightning and surge arrester Type 1+2 to DIN EN 61643-11 (B+C to VDE 0675 Part 6).

- With new Multibase base with multi connection terminals
- Complete unit consisting of cover and base, pre-mounted and ready for connection
- For TN systems
- Plug-in arrester with dynamic isolating device
- With visual function display
- Protection level <1.5 kV
- Encapsulated non-extinguishing zinc oxide varistor arrester for use in standard distributor housings
- Marked connections


Application example: Building with open-wire power supply or for setting up lightning protection equipotential bonding in residential buildings.

Dimensions



Type	Highest continuous voltage V	Version	Pack. pcs	Weight kg/100 pcs.	Item No.
V25-B+C 3-385	385	3-pole complete	1	42,000	5094 43 7

Connection options



V25-B+C 3-385

Nominal voltage V	U_N	350
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350) kA	I_{imp}	7
Total discharge current (10/350) kA	I_{total}	21
Nominal discharge current (8/20) kA	I_n	30
Arrester surge current (8/20) [total] kA	$I_{Total 8/20}$	90
Maximum discharge current (8/20 μ s) kA	I_{max}	50
		—
Voltage protection level kV	U_p	<1,5
Response time ns	t_A	< 25
Maximum back-up fuse A		160
Temperature range °C	ϑ	-40-80
Division unit TE (17.5 mm)		3
Protection rating		IP20
Connection cross-section rigid mm ²		2,5-35
Connection cross-section, multi-wire mm ²		2,5-35
Connection cross-section, flexible mm ²		2,5-25