

Koblingsklemme for Al/Cu


KVIAC11095

6 - 95 mm²
KVIAC12095

6 - 95 mm²
KVIAC11150

25 - 150 mm²
KVIAC12150

25 - 150 mm²

Farge / ELNr	GRÅ	●	12 041 02	12 041 16	12 041 70	12 041 73
	BLÅ	●	12 041 03	12 041 17	12 041 71	12 041 74
	Gul/Grønn	●●	12 041 04	12 041 18	12 041 72	12 041 75

NORM	SFS 2663	SFS 2663	SFS 2663	SFS 2663
SERTIFIKAT	CE, UL1059, SGS	CE, UL1059, SGS	CE, UL1059, SGS	CE, UL1059, SGS
KABELVERRSNITT Al/Cu Kabel	6 - 95 mm ²	2 X 6 - 95 mm ²	25 - 150 mm ²	2 X 25 - 150 mm ²
SPENNING	690 V	690 V	690 V	690 V
STRØM	245 A	490 A	320 A	640 A
TILTREKNINGSMOMENT	6 - 25mm ² 12 Nm 35 - 95mm ² 22 Nm	6 - 25mm ² 12 Nm 35 - 95mm ² 22 Nm	25 - 50mm ² 14 Nm 70 - 150mm ² 30 Nm	25 - 50mm ² 14 Nm 70 - 150mm ² 30 Nm
MONTERING	DIN / SKRUE	DIN / SKRUE	DIN / SKRUE	DIN / SKRUE
VEKT	65g	125g	100g	170g
ANTALL / PAK.	20 ○ 10 ● 10 ●●	30 ○ 15 ● 15 ●●	20 ○ 10 ● 10 ●●	10 ○ 5 ● 5 ●●
MÅL	L=84, L1=56, L2=35 L3=72, H=51, H1=11 H2=16, H3=5, W=25, W1=13, AV=5	L=84, L1=56, L2=35 H=51, H1=11, H2=16, H3=5, W=42, W1=13, W2=17,5, AV=5, D=5,5	L=84, L1=56, L2=35 L3=72, H=54, H1=11 H2=20, H3=5, W=31, W1=18,5, AV=5	L=84, L1=56, L2=35 H=54, H1=11, H2=20, H3=5, W=51, W1=18,5, W2=21, AV=5
ARBEIDSTEMPERATUR				

