

# LANmark Patchpaneler for Snap-in konnektorer

## Patchpanel Vinklet 24 Snap-in Sort

Kontakt  
Nexans Cabling Solutions  
firmapost@nexans.com

Nexans ref.: N521.671

El. nummer: 6916997

- Støtter høy tetthetspatching - ideell for datasentre
- Eliminerer behovet for ekstra kabelhåndtering
- Opptil dobbelt tetthet oppnåelig
- Kompatibel med alle Snap-In konnektorer
- Eksklusivt Auto-Connect jordingssystem
- Universell design som støtter uskjærmede og skjærmede konnektorer
- Finnes også i hvitt

### BESKRIVELSE

Nexans Snap-In range of patch panels are designed to accomodate any of the Snap-In connectors in the LANmark product family (LANmark-7A, LANmark-7, LANmark-6A, LANmark-6, and LANmark-5).

The Snap-In panels feature an exclusive Clip-On system to secure the connector in the panel and to provide a simple means of earthing shielded connectors to facilitate installation. Connection of the panel to earth is achieved with a unique Auto-Connect feature removing the need for individual bonding conductors.

The panels also have a series of complementary cable management products such as blank panels and patch cord guides.

The patch panels are designed for standard 19" enclosures, are 1U high, and support the following features:

- Improved patching density
- 24 unloaded ports with shutters, up to 912 ports in a 42 HU cabinet
- Used with open rack frames or closed/open cabinets providing vertical cabling management
- Printed numbering system as port labelling
- Rear cable management support included
- Designed for shielded and unshielded Snap-In connectors
- Clip-On mechanism to provide quick and secure earthing for shielded connectors



# LANmark

### STANDARDE

Internasjonal  
Manufacturer specification

# LANmark Patchpaneler for Snap-in konnektorer

Patchpanel Vinklet 24 Snap-in Sort

## Kontakt

Nexans Cabling Solutions  
firmapost@nexans.com

## EGENSKAPER

### Konstruksjonsegenskaper

|           |       |
|-----------|-------|
| Farge     | Svart |
| Materiale | Steel |

### Dimensjonsegenskaper

|        |        |
|--------|--------|
| Høyde  | 1 U    |
| Dybde  | 120 mm |
| Bredde | 19 in  |

### Bruksegenskaper

|               |                      |
|---------------|----------------------|
| Bruksområde   | Faste installasjoner |
| Antall porter | 24                   |
| Forpakning    | Eske                 |